

SylBay - SylSmart
Sylbay 4000K L2 19500LM WIDE SSE
0040342



Product features

- Logistics and Industry modular high bay luminaire with wide optics to provide homogenous light distribution for open space areas. Single body with 2 optical modules, 19000 lumens, 135W, 141lm/W, 4000K, CRI 80, wide beam optic, 3 step MacAdam ellipse, grey finish (RAL7012), Class 1, 220-240V, IP65, IK08 (Sensor IK03), (LxWxH) 505x386x133mm, Mains + control cable of 2 meter, SylSmart Connected Industry enabled.




PRODUCT OVERVIEW

Product name	Sylbay 4000K L2 19500LM WIDE SSE
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
ETIM Class	EC001716
Warranty	5 years
Fixture luminous flux (lm)	19000
Luminaire efficacy (lm/W)	141
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	75
Glare control	< 22
Photobiological Risk Group	RG1
Total power consumption (W)	135
Electrical protection	Class I
Control gear type	LED driver constant current
Control gear mounting	Integral
Dimmable	Yes
Dimming method	SylSmart SSE
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288403427

SylBay - SylSmart
Sylbay 4000K L2 19500LM WIDE SSE
0040342

PHOTOMETRY



TECHNICAL DRAWINGS

