

36PG-2022P: Press adapter to copper press Gas 20x22



Commercial information

De fittingen zijn voorzien van een speciale O-ring, Deze O-ring is gemaakt van het materiaal HNBR en is bestand tegen gas.

- Persovergang van koper naar Henco pers
- Snellere en meer zekere verwerking door persverbindingaan koperzijde in tegenstelling tot een knelverbinding.
- Koperzijde geschikt voor M --, V en SA profiel persbekken
- Toegelaten om te gebruiken op moeilijkbereikbare plaatsen
- Koppeling mag ingestort worden mits beschermend verpakt
- Legering CW617 "m"
- Compatibel met dunwandig staal, koper en inox

Basic unit dimensions

Height	32 mm
Length	59 mm
Width	32 mm
Net weight	0.092 kg

Certificates

GASTEC, DVGW Gas

Applications

Gas

Solutions

Building installations, Industry, Oil & gas, Utility, Shipbuilding

Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Material quality connection 1	CuZn40Pb2 (CW617N)	Outer pipe diameter connection 1	20 Millimetre
Surface protection connection 1	Untreated	Outer pipe diameter connection 2	22 Millimetre
Surface treatment connection 1	Untreated	Length	59 Millimetre
Material connection 2	Brass	Length of connection 1	29 Millimetre
Material quality connection 2	CuZn40Pb2 (CW617N)	Working length connection 1	25 Millimetre
Surface protection connection 2	Untreated	Length of connection 2	26.5 Millimetre
Surface treatment connection 2	Untreated	Working length connection 2	22.5 Millimetre
Shape	Straight	Wrench width	0 Millimetre
Reducing	✗	Wrench width union nut	0 Millimetre
Eccentric	✗	Medium temperature (continuous)	-10 60 Degrees celsius
System specific	✓	Max. operating pressure at 20 °C	10 Bar
Connection 1	Press sleeve	Standard Dimension Ratio (SDR)	0
Contour code connection 1	TH		
Connection 2	Press sleeve		
Contour code connection 2	M/F (seal) (expired)		
Main colour fitting	Brass		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✓		
High tensile strength	✗		
With thermal insulation	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✗		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✓		
DVGW quality mark for water	✗		
KIWA certified	✗		
Gastec QA mark	✓		
KOMO certified	✗		
Type approval according to BBR/EKS	✗		