

Sylvania Granit IP65 0-10V 32000lm 865 WB

Item No: 0039741




PRO



Technical Assets


Dimensions (mm)



Photometrics

Distance [m]	Cone diameter [m]	E(0°) [lx]	E(C0) [lx]
0.5	0.86	90234	19688
1.0	1.73	22555	4897
1.5	2.59	10005	2178
2.0	3.45	5640	1241
2.5	4.32	3609	784
3.0	5.19	2605	544

Distance [m] Cone diameter [m]
C0 - C180 (Half beam angle: 51.6°)



Sylvania Granit IP65 0-10V 32000lm 865 WB

Item No: 0039741

SYLVANIA

General data

Product name	Sylvania Granit IP65 0-10V 32000lm 865 WB
Technology	LED
Cap/Base	N/A
General application	Logistics & Industry
Operating temperature range (°C)	-30°C...+50°C
ETIM Class	EC001716
Warranty	5 years

Optical data

Fixture luminous flux (lm)	32000
Luminaire efficacy (lm/W)	160
Correlated colour temperature (k)	6500
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	85
Distribution type	Symmetric
Glare control	< 25
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	200
Primary Supply/Product voltage - min (V)	220.0
Lamp power factor	0.95
Electrical protection	Class I
Dimming method	0-10V
Drive current (mA)	780
Inrush Current (A)	100
Inrush Duration (µs)	300
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. products per 10A C Breaker	4
Max. products per 13A C Breaker	5
Max. products per 16A C Breaker	7
Max. products per 20A C Breaker	9
Max. products per 20A B Breaker	5
Mains surge immunity (differential mode -> L-N) (kV)	6
Mains surge immunity (common mode -> L/N - GND) (kV)	6

Lifetime data

Lifespan L70 B50	120000
Lifespan L80 B20	92000
Lifespan L90 B50	51000

Physical data

Housing colour	RAL 9017 - Traffic black
IP rating	IP65
IK rating	IK08
Nominal Product Height (mm)	163
Nominal Product Diameter (mm)	370
Weight (kg)	2.865

Sylvania Granit IP65 0-10V 32000lm 865 WB

Item No: 0039741



Packaging

Product EAN number	5410288397412
Packaging single width (cm)	40.0
Packaging single depth (cm)	14.5
DUN14 (inner)	05410288397412
Packaging outer length / height (cm)	40.0

Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-30-50