


# Giotto LED 305

*GIOTTO 305 3000K RECESSED MW SENSOR*  
3034775



## Product features

- Ambient and decorative round, recessed mounted LED bulkhead luminaire. White robust polycarbonate body with opal diffuser, 1625lm, 14.7W, 111lm/W, 3000K, CRI 80, non-dimmable, integral microwave sensor. 120,000 hours lumen maintenance (L70:B50). Drive current: 600mA, IP44, IK10, Class I, 220-240V.




## PRODUCT OVERVIEW

|                                 |                                     |
|---------------------------------|-------------------------------------|
| Product name                    | GIOTTO 305 3000K RECESSED MW SENSOR |
| Technology                      | LED                                 |
| Cap/Base                        | N/A                                 |
| Housing                         | PC Polycarbonate                    |
| Mount                           | Ceiling recessed mounting           |
| Environment                     | Indoor                              |
| General application             | Hospitality, Logistics & Industry   |
| ETIM Class                      | EC002892                            |
| E-number FI                     | 4225704                             |
| Warranty                        | 5 years                             |
| Fixture luminous flux (lm)      | 1625                                |
| Luminous flux (lm)              | 1625                                |
| Luminaire efficacy (lm/W)       | 111                                 |
| Colour temperature (K)          | 3000                                |
| Colour Code                     | 830                                 |
| Light colour                    | Warm White                          |
| CRI (Ra)                        | 80                                  |
| Colour Variation Initial (SDCM) | SDCM3                               |
| Beam Angle (°)                  | 120                                 |
| Glare control                   | < 24                                |
| Photobiological Risk Group      | RG0                                 |
| Total power consumption (W)     | 14.7                                |
| Electrical protection           | Class I                             |
| Control gear type               | LED driver constant current         |
| Control gear mounting           | Integrated                          |
| Dimmable                        | No                                  |
| Dimming method                  | N/A                                 |
| LED Flickering Rate             | Ultra low (5% or less)              |
| Housing colour                  | White                               |
| IP rating                       | IP44                                |
| IK rating                       | IK10                                |
| Product EAN number              | 8711971347750                       |

# Giotto LED 305

*GIOTTO 305 3000K RECESSED MW SENSOR*  
3034775

## PHOTOMETRY



## TECHNICAL DRAWINGS

