


Data Sheet | Item Number: 294-5255

Lighting connector; push-button, external; with snap-in ground contact; 5-pole;
Lighting side: for solid conductors; Inst. side: for all conductor types; max. 2.5 mm²;
Surrounding air temperature: max 85°C (T85); 2,50 mm²; white

<https://www.wago.com/294-5255>



Color: white



Dimensions in mm

- External connection of solid, stranded and fine-stranded conductors
- Universal conductor termination (AWG, metric)
- Third contact located at the bottom of internal connection end
- Strain relief plate can be retrofitted

Electrical data									
Ratings per		IEC/EN 60998-1			Ratings per		IEC/EN 60998-2-2		
Overvoltage category		III	III	II	Overvoltage category		III	III	II
Pollution degree		3	2	2	Pollution degree		3	2	2
Nominal voltage		-	-	500 V	Nominal voltage		-	-	500 V
Rated surge voltage		-	-	4 kV	Rated surge voltage		-	-	4 kV
Rated current		-	-	24 A	Rated current		-	-	24 A

Connection data		
Connection points	25	Connection 1 Connection type 1 External 1 Connection technology Push-in CAGE CLAMP® Number of connection points 2 Actuation type Push-button Connectable conductor materials Copper Solid conductor 0.5 ... 2.5 mm² / 18 ... 12 AWG Solid conductor; push-in termination 0.5 ... 2.5 mm² / 18 ... 12 AWG Stranded conductor 0.5 ... 2.5 mm² / 18 ... 14 AWG Fine-stranded conductor 0.5 ... 2.5 mm² / 18 ... 14 AWG Fine-stranded conductor; with insulated ferrule 0.5 ... 1.5 mm² / 18 ... 16 AWG Fine-stranded conductor; with uninsulated ferrule 0.5 ... 1.5 mm² / 18 ... 16 AWG Fine-stranded conductor; with ferrule; push-in termination 0.5 mm² / 18 AWG Strip length 8 ... 9 mm / 0.31 ... 0.35 inches Pole number 5 Wiring direction Side-entry wiring
Total number of potentials	5	
Number of connection types	4	
PE function	Snap-in PE contact	



Connection 2	
Connection type 2	Internal 2
Connection technology 2	PUSH WIRE®
Number of connection points 2	1
Actuation type 2	Push-in
Solid conductor 2	0.5 ... 2.5 mm² / 18 ... 14 AWG
Fine-stranded conductor; with insulated ferrule 2	0.5 ... 1 mm² / 18 ... 16 AWG
Fine-stranded conductor; with uninsulated ferrule 2	0.5 ... 1.5 mm² / 18 ... 14 AWG
Strip length 2	8 ... 9 mm / 0.31 ... 0.35 inches

Connection 4	
Connection type 4	Internal 4
Connection technology 4	PUSH WIRE®
Number of connection points 4	1
Actuation type 4	Push-in
Solid conductor 4	0.5 ... 0.75 mm² / 18 AWG
Strip length 4	8 ... 9 mm / 0.31 ... 0.35 inches

Physical data		
Pin spacing		10 mm / 0.394 inches
Width		50 mm / 1.969 inches
Height		21.53 mm / 0.848 inches
Height from the surface		17 mm / 0.669 inches
Depth		27.3 mm / 1.075 inches

Mechanical data	
Marking	3-N- -1-2
Mounting type	Snap-in foot

Material data	
Note (material data)	Information on material specifications can be found here
Color	white
Material group	IIa
Insulation material	Polycarbonate (PC)
Flammability class per UL94	V0
Clamping spring material	Chrome-nickel spring steel (CrNi)
Contact material	Electrolytic copper (E _{Cu})
Contact plating	Tin
Fire load	0.302 MJ
Halogen-free	Yes
Weight	16.3 g



Environmental requirements	
Temperature stability	120 °C
T marking	T85
Commercial data	
Product Group	8 (Misc. Chassis Mount Blocks)
eCl@ss 10.0	27-14-11-06
eCl@ss 9.0	27-14-11-06
ETIM 8.0	EC001284
ETIM 7.0	EC001284
PU (SPU)	250 pcs
Packaging type	Bag
Country of origin	PL
GTIN	4050821098461
Customs tariff number	85369010000
Environmental Product Compliance	
CAS-No.	131651-65-5 144317-44-2 220133-51-7 220689-12-3 25628-08-4 29420-49-3 375-73-5 503155-89-3 507453-86-3 68259-10-9
REACH Candidate List Substance	Perfluorobutane sulfonic acid (PFBS) and its salts
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c) 7(a) 7(c)-I 7(c)-II
SCIP notification number (Austria)	a26b284d-70d7-495a-a387-df6ffeee34e1
SCIP notification number (Belgium)	15eeaaeb-2641-46bb-a92f-44abd0142320
SCIP notification number (Bulgaria)	d521f7ea-f797-4e4b-bfa9-8af38d4a28ee
SCIP notification number (Czech Republic)	23815bd0-6834-460e-9b88-0420dc81191e
SCIP notification number (Denmark)	7274aaa1-bc75-4225-8705-6889e7ff236a
SCIP notification number (Finland)	c63f4031-d1a8-456a-ac6a-c82c2eb8e731
SCIP notification number (France)	33da5adc-36f7-47b1-af99-b0cad079fdf3
SCIP notification number (Germany)	90482978-d9ed-4a8e-876c-0d155b9b9b9c
SCIP notification number (Hungary)	1b78c562-1359-4bb9-95f3-a6c64119d2e4
SCIP notification number (Italy)	0bd65ab1-9a4e-4c3a-904b-7e02bd801b59
SCIP notification number (Netherlands)	413c9a5d-99ba-4b34-8567-625a6935d00d
SCIP notification number (Poland)	2129cbf8-8da1-44ff-8c30-f6513f51a5e8
SCIP notification number (Romania)	b2dd3e27-66de-456a-9988-b0d3d76f11f8
SCIP notification number (Sweden)	b0f6caac-86a0-4c0d-927c-8a51eccea703



Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
ENEC 05 DEKRA Certification B.V.	EN 60998	2128791.01

Declarations of conformity and manufacturer's declarations

Approval	Standard	Certificate Name
EU-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-
UK-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-

Downloads

Environmental Product Compliance

Compliance Search
Environmental Product Compliance 294-5255



Documentation

Additional Information
Technical Section
pdf 2240.62 KB



Bid Text
294-5255
13.06.2017
doc 28.50 KB
294-5255
19.02.2019
xml 5.58 KB



CAD/CAE-Data

CAD data
2D/3D Models 294-5255



CAE data
WSCAD Universe 294-5255
ZUKEN Portal 294-5255



1 Compatible Products

1.1 Optional Accessories

1.1.1 Strain relief

1.1.1.1 Strain relief



[Item No.: 294-370](#)
Strain relief; for 294 Series; with snap-in mounting feet; white



[Item No.: 294-375](#)
Strain relief; for 294 Series; without snap-in mounting feet; white

1.1.1.2 Strain relief plate



Item No.: 294-364

Strain relief plate; for 294 Series; for multi-core cables; 3- to 5-pole; with secured clamp; white

Item No.: 294-384

Strain relief plate; for 294 Series; for single strands; 3- to 5-pole; with secured clamp; white

1.1.2 Tool

1.1.2.2 Operating tool






Item No.: 206-294

Disconnection tool; green

Installation Notes

Installation




5-pole – with snap-in ground contact, d = 4.9 mm

Snap-in foot


Drilled hole for snap-in mounting foot

Conductor termination




EUROPE
1x 0.5 ... 2.5 mm ² "s"
1x 0.5 ... 1.5 mm ² "s"
1x 0.5 ... 0.75 mm ² "s"
AMERICA
1x AWG 18 ... 14 "s"
1x AWG 18 ... 16 "s"
1x AWG 18 "s"
JAPAN
1x 0.8 ... 1.6 mm diam. "s"
1x 0.8 ... 1 mm diam. "s"
1x 0.8 mm diam. "s"

EUROPE
2 x 0.5 ... 2.5 mm**s, str, f-str*
AMERICA
2 x AWG 18 ... 12 "s"
2 x AWG 18 ... 14 "s, f-str*
JAPAN
2 x 0.8 ... 2 mm diam. "s"
2 x 0.5 ... 2 mm** "str, f-str"



Internal connection:
PUSH WIRE® for internal wiring with solid conductors



External connection:
Push-in CAGE CLAMP® for field-wiring
with all conductor types

Terminating five conductors per pole – solid and fine-stranded.

