

START Downlight Eco 95mm Round Recessed

START Downlight Eco 95 640lm 830
0053910



Product features

- START Downlight Eco is an integrated LED recessed downlight with built-in non dimmable driver; Loop in loop out connector allows for quick installation; 8W; 640Lm; 80Lm/W; 3000K.



PRODUCT OVERVIEW

Product name	START Downlight Eco 95 640lm 830
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
General application	Retail
ETIM Class	EC001744
Warranty	3 years
Useful luminous flux (Fuse)	640
Fixture luminous flux (lm)	640
Luminaire efficacy (lm/W)	80
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	110
Glare control	< 28
Photobiological Risk Group	RG0
Total power consumption (W)	8
Electrical protection	Class II
Dimmable	No
Dimming method	N/A
LED Flickering Rate	Medium (21% - 40%)
Housing colour	RAL 9003 - Signal white
IP rating	IP20
IK rating	IK02
Product EAN number	5410288539102

PHOTOMETRY


START Downlight Eco 95mm Round Recessed

START Downlight Eco 95 640lm 830
0053910

Distance [m]	Cone diameter [m]	E07	E07 E07	E07 E07
0.5	1.56 1.56	390	71	71
1.0	3.12 3.13	222	15	17
1.5	4.67 4.69	99	6	6
2.0	6.23 6.25	66	4	4
2.5	7.79 7.82	36	3	3
3.0	9.35 9.38	25	2	2

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 114.6°)
— C90 - C270 (Half beam angle: 114.6°)



TECHNICAL DRAWINGS

