

## VBS050504-BL: Manifold 3/4" with valves and eurocone connection 3/4"x4xEK14,16,18 &



### Commercial information

- O-ring connection + alignment
- Universal euroconus connections
- Lockable by circuit
- Short installation length
- Can be installed both vertical, horizontal or upside down
- Available in a 3/4" and a 1" version
- Available in red and blue. Optionally green levers are available.
- Suitable for the realization of heating, air conditioning and sanitary installations
- Manifolds configuration permit the realization of hot and/or cold circuits in parallel.

### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 75 mm    |
| Length     | 190 mm   |
| Width      | 45 mm    |
| Net weight | 0.660 kg |

### Certificates

### Applications

Potable water, Heating, Cooling, Sanitary

### Solutions

Building installations, Industry, Utility

## Technical characteristics

|                                    |                                                            |                                      |                    |
|------------------------------------|------------------------------------------------------------|--------------------------------------|--------------------|
| Suitable for tap water             | ✓                                                          | Number of branches                   | 4                  |
| Suitable for central heating water | ✓                                                          | Number of branching directions       | 1                  |
| Suitable for cooling water         | ✓                                                          | Distance between offset              | 45 Millimetre      |
| Suitable for compressed air        | ✗                                                          | Max. medium temperature (continuous) | 95 Degrees celsius |
| Suitable for glycol                | ✓                                                          | Width                                | 45 Millimetre      |
| Mounting method                    | Surface mounting                                           | Height                               | 75 Millimetre      |
| Model                              | Distributor/collector                                      | Length distributor                   | 190 Millimetre     |
| Material                           | Brass                                                      |                                      |                    |
| Surface protection                 | Untreated                                                  |                                      |                    |
| Shape                              | Other                                                      |                                      |                    |
| Nominal diameter connection 2      | 3/4 inch (20)                                              |                                      |                    |
| Connection 2                       | Internal thread cylindrical BSPT-Rp (ISO 7-1 / EN 10226-1) |                                      |                    |
| Nominal diameter branches          | 3/4 inch (20)                                              |                                      |                    |
| Connection branches                | Euroconus (expired)                                        |                                      |                    |
| Deviant distance between branches  | ✗                                                          |                                      |                    |
| With filling/drain tap             | ✗                                                          |                                      |                    |
| System specific                    | ✓                                                          |                                      |                    |
| With shut-off valve                | ✗                                                          |                                      |                    |
| With de-aeration                   | ✗                                                          |                                      |                    |
| With wall-mounting bracket         | ✗                                                          |                                      |                    |
| With mounting material             | ✗                                                          |                                      |                    |
| With legs                          | ✗                                                          |                                      |                    |
| With insulation                    | ✗                                                          |                                      |                    |
| KOMO certified                     | ✗                                                          |                                      |                    |
| Type approval according to BBR/EKS | ✗                                                          |                                      |                    |