



ISO-BLOCK-S: Henco carcassing pipe Ø 16 with insulation



Commercial information

Certificates

Applications

Potable water, Heating, Cooling, Compressed air, Demi Water, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Material intermediate layer	Plastic	Outer pipe diameter	16 Millimetre
Material outer layer	Plastic	Wall thickness	2 Millimetre
Glass-fibre reinforced		Medium temperature (continuous)	- Degrees celsius
	✘		10 7 0
Diffusion-proof	✘	Max. operating pressure at 20 °C	16 Bar
Nominal diameter	DN 12	Max. operating pressure at max. medium temperature	16 Bar
System specific	✓	Wall roughness	0.00 Millimetre 7
Flexible	✘	Expansion coefficient	0.02 Millimetre per metre Kelvin 5
Suitable for surface mounting	✘	Outer diameter mantle pipe	0 Millimetre
Pipe colour	White	Thickness of thermal insulation	0 Millimetre
With mantle pipe	✘	Lambda value	0.43 Watt per meter Kelvin
With heating cable	✘	Outer diameter thermal insulation	0 Millimetre
With thermal insulation	✘	Outer width rectangular insulation	0 Millimetre
Capped	✘	Outer height rectangular insulation	0 Millimetre
UV resistant	✘		
Halogen free	✓		
DIN-CERTCO certificate	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✓		
KOMO certified	✓		
Type approval according to BBR/EKS	✘		

Related products