


# Concord

## Solstice 200 2000lm 930 DALI Sandblast 2070416



### Features

- Solstice 200 2000lm 930 DALI Sandblast is an efficient DALI dimmable downlight luminaire, Colour rendering index Ra>90, Colour temperature: 3000K Warm White, Class II, Protection rating IP40/IP20, Cut out dimensions: 150mm.

### Product Overview


Product name	Solstice 200 2000lm 930 DALI Sandblast
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
Fixture luminous flux (lm)	2000
Luminaire efficacy (lm/W)	135
LOR (%)	118
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	90
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Glare control	< 19
Photobiological Risk Group	RG1
Total power consumption (W)	17
Electrical protection	Class II
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)

# Concord

## Solstice 200 2000lm 930 DALI Sandblast 2070416

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP40/20
IK rating	IK02
Product EAN number	5025768704163
Warranty	5 years
Useful luminous flux (#use)	2000

### Photometry



### Technical drawings

