


Sylbay 4000K L4 32000LM WIDE DALI


Item No: 0040310





Logistics and Industry modular high bay luminaire with wide optics to provide homogenous light distribution for open space areas. Twin body with 4 optical modules, 31000 lumens, 205W, 156lm/W, 4000K, CRI 80, wide beam optic, DALI dimmable, 3 step MacAdam ellipse, grey finish (RAL7012), Class 1, 220-240V, IP65, IK08, (LxWxH) 726x386x133mm, Mains + control cable of 2 meter.

Technical Assets

Dimensions (mm)



Photometrics



Sylbay 4000K L4 32000LM WIDE DALI

Item No: 0040310



General data

Product name	Sylbay 4000K L4 32000LM WIDE DALI
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
Operating temperature range (°C)	-40°C...+50°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001716
Warranty	5 years

Optical data

Useful luminous flux (Φuse)	31000
Fixture luminous flux (lm)	31000
Luminaire efficacy (lm/W)	156
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Beam Angle (°)	75
Glare control	< 22
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	205
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.98
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	5.1
Electrical protection	Class I
Control gear required	No
Control gear type	Electronic ballast
Control gear mounting	Integral
Dimmable	Yes
Dimming method	DALI
Drive current (mA)	700
Inrush Current (A)	65
Inrush Duration (µs)	268
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	5
Max. products per 13A C Breaker	7
Max. products per 16A C Breaker	8
Max. products per 20A C Breaker	10
Max. products per 10A B Breaker	3
Max. products per 13A B Breaker	4
Max. products per 16A B Breaker	5
Max. products per 20A B Breaker	6

Lifetime data

Lifespan L70 B50	120000
Lifespan L80 B20	120000
Lifespan L90 B10	52000

Sylbay 4000K L4 32000LM WIDE DALI

Item No: 0040310



Physical data

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	726
Nominal Product Width (mm)	386
Nominal Product Height (mm)	133
Weight (kg)	8.07

Packaging

Product EAN number	5410288403106
Packaging single length / height (cm)	92.0
Packaging single width (cm)	47.5
Packaging single depth (cm)	27.0
DUN14 (inner)	05410288403106
Units per outer package	1
Packaging outer length / height (cm)	92.0
Packaging outer width (cm)	47.5
Packaging outer depth (cm)	27.0

Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-40-50