


VISION SET 26: Vision set Ø 26 (sleeve + 2 O-rings)



Commercial information

Henco revision set contains 2 O-rings and sleeve

Basic unit dimensions

Height	39 mm
Length	38 mm
Width	39 mm
Net weight	0.031 kg

Certificates

QB (CSTBat), DVGW Wasser, ETA, KIWA, ÖVGW Wasser, SINTEF, SITAC, WRAS, KOMO, STF, GOST-R, TSU, EMI

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Material	Plastic	Bend radius	0 Millimetre
Material connection 1	Polyvinylidene fluoride (PVDF)	Outer pipe diameter connection 1	26 Millimetre
Material quality	Polyvinylidene fluoride (PVDF)	Length	38 Millimetre
Material quality connection 1	Polyvinylidene fluoride (PVDF) (expired)	Wrench width union nut	0 Millimetre
Surface protection connection 1	Untreated	Medium temperature (continuous)	-10 70 Degrees celsius
Surface treatment connection 1	Untreated	Max. operating pressure at 20 °C	10 Bar
Material connection 2	Polyvinylidene fluoride (PVDF)	Standard Dimension Ratio (SDR)	0
Material quality connection 2	Polyvinylidene fluoride (PVDF) (expired)		
Surface protection connection 2	Untreated		
Surface treatment connection 2	Untreated		
Reducing	✗		
Eccentric	✗		
System specific	✓		
Connection 1	Insert (push-fitting)		
Main colour fitting	White		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✗		
Self-sealing	✗		
With thermal insulation	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✗		
With connection indicator	✗		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✓		
KIWA certified	✓		
Gastec QA mark	✗		
KOMO certified	✓		
Type approval according to BBR/EKS	✗		