


Sylvania Granit IP65 DALI 13000lm 840 WB

Item No: 0039752




PRO



Technical Assets


Dimensions (mm)



Photometrics

Distance [m]	Cone diameter [m]	E(0°) [lx]	E(0°) [lx]	E(0°) [lx]
0.5	0.89	34285	418°	7130
1.0	1.79	8564	418°	1783
1.5	2.68	3696	418°	792
2.0	3.58	2141	418°	448
2.5	4.47	1370	418°	285
3.0	5.36	962	418°	196

Distance [m] Cone diameter [m]
C0 - C180 (Half beam angle: 83.6°)



Sylvania Granit IP65 DALI 13000lm 840 WB

Item No: 0039752

SYLVANIA

General data

Product name	Sylvania Granit IP65 DALI 13000lm 840 WB
Technology	LED
Cap/Base	N/A
General application	Logistics & Industry
Operating temperature range (°C)	-30°C...+50°C
ETIM Class	EC001716
E-number FI	4357105
Warranty	5 years

Optical data

Fixture luminous flux (lm)	13000
Luminaire efficacy (lm/W)	163
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	85
Distribution type	Symmetric
Glare control	< 25
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	80
Primary Supply/Product voltage - min (V)	220.0
Lamp power factor	0.95
Electrical protection	Class I
Dimming method	DALI-2
Drive current (mA)	410
Inrush Current (A)	77
Inrush Duration (µs)	102
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. products per 10A C Breaker	16
Max. products per 13A C Breaker	20
Max. products per 16A C Breaker	27
Max. products per 20A C Breaker	32
Max. products per 20A B Breaker	20
Mains surge immunity (differential mode -> L-N) (kV)	6
Mains surge immunity (common mode -> L/N - GND) (kV)	6

Lifetime data

Lifespan L70 B50	120000
Lifespan L80 B20	92000
Lifespan L90 B50	51000

Physical data

Housing colour	RAL 9017 - Traffic black
IP rating	IP65
IK rating	IK08
Nominal Product Height (mm)	168
Nominal Product Diameter (mm)	298
Weight (kg)	2.243

Sylvania Granit IP65 DALI 13000lm 840 WB

Item No: 0039752



Packaging

Product EAN number	5410288397528
Packaging single width (cm)	32.5
Packaging single depth (cm)	14.5
DUN14 (inner)	05410288397528
Packaging outer length / height (cm)	32.5

Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-30-50