


## UFH-0505SSTN11-PN6: 11-groups steel collect. with pump, district heating nuon PN6



### Commercial information

- Steel distributor for residential construction where the energy supplier is Nuon or Eneco
- This distributor is suitable for both main and auxiliary heating at various HR boilers (according to GIW/ISSO 2007 regulations)
- Supply and return of the groups are on top of each other for a good and smooth connection
- Outputs are connected euro cone 3/4"

### Basic unit dimensions

Height	440 mm
Length	190 mm
Width	840 mm
Net weight	0.001 kg

### Certificates

#### Applications

Heating, Cooling, Underfloor Heating

#### Solutions

Underfloor heating, Building installations, Industry, Energy/district heating, Utility

## Technical characteristics

Connection type primary side	2-pipe	Outer pipe diameter primary connection	32 Millimetre
Suitable for cooling	✓	Medium temperature (continuous)	10 60 Degrees celsius
Material	Steel	Max. operating pressure	6 Bar
Position primary connection	Top	Max. number of expansion groups	0
Primary connection	Internal thread cylindrical BSPP-G (ISO 228-1)	Supply voltage	230 Volt
Nominal diameter primary connection	3/4 inch (20)	Number of groups secondary	11
With valves on primary connection	✓	Outer pipe diameter secondary	12 20 Millimetre
With mixing valve	✓	Flow-through capacity	0 4.5 Litre per hour
Expandable	✗	Min. pressure difference secondary flow/return	0 Kilo Pascal
Multi-zone manifold	✗	Width	840 Millimetre
With temperature limit	✓	Height	440 Millimetre
With non-return valve	✓	Depth	190 Millimetre
With circulation pump	✓		
Type of pump (system pump)	AC		
Article compression class	PN 6		
With controller	✓		
Hydraulic balance control	Static		
Volume flow measurement	None		
With thermometer	✓		
Temperature measurement supply	Analogue		
Temperature measurement return	Analogue		
With de-aeration	✓		
With pressure gauge	✗		
Secondary connection	Euroconus standardless		
Nominal diameter secondary connection	3/4 inch (20)		
Closable groups	✓		
With flow-through indicator	✗		
With thermal actuator	✗		
With wall-mounting bracket	✓		
With casing	✗		