

VVPK-20: Straight entry piece - Press Ø20



Commercial information

Straight entry piece - Press

Basic unit dimensions

Height	28 mm
Length	67 mm
Width	28 mm
Net weight	0.036 kg

Certificates

QB (CSTBat), DVGW Wasser, ETA, KIWA, ÖVGW Wasser, SINTEF, SITAC, WRAS, KOMO, STF, GOST-R, EMI, TSU

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Material connection 1	Polyvinylidene fluoride (PVDF)	Bend angle	90 Degrees
Material quality connection 1	Polyvinylidene fluoride (PVDF) (expired)	Bend radius	0 Millimetre
Surface protection connection 1	Untreated	Outer pipe diameter connection 1	20 Millimetre
Surface treatment connection 1	Untreated	Wall thickness, connection 1	0.7 Millimetre
Material connection 2	Polyvinylidene fluoride (PVDF)	Length	66.6 Millimetre
Material quality connection 2	Polyvinylidene fluoride (PVDF) (expired)	Wrench width	0 Millimetre
Surface protection connection 2	Untreated	Wrench width union nut	0 Millimetre
Surface treatment connection 2	Untreated	Medium temperature (continuous)	-10 70 Degrees celsius
Shape	Straight	Max. operating pressure at 20 °C	10 Bar
Model	1-part	Standard Dimension Ratio (SDR)	0
Reducing	✘		
Eccentric	✘		
System specific	✓		
Connection 1	Press sleeve		
Main colour fitting	White		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✓		
High tensile strength	✘		
With thermal insulation	✘		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✘		
With drain valve	✘		
With de-aerator	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
DIN-CERTCO certificate	✘		
VdS quality mark	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✓		
KIWA certified	✓		
Gastec QA mark	✘		
KOMO certified	✓		
Type approval according to BBR/EKS	✘		