

Specifications



Photo is representative



Eaton KLM-3

Eaton Bussmann series KLM fuse, 3 A, Non-indicating, Ferrule end x ferrule end, 100 kAIC at 600 V, 50 kAIC at 600 Vdc, Nickel-plated bronze endcap, Melamine tube, 600 V, 600 Vdc

General specifications

PRODUCT NAME	Eaton Bussmann series KLM fuse
CATALOG NUMBER	KLM-3
UPC	051712695107
EAN	5027590445382
PRODUCT LENGTH/DEPTH	0.001 in
PRODUCT HEIGHT	0.001 in
PRODUCT WIDTH	0.001 in
PRODUCT WEIGHT	0.18 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant CE Marked
PRODUCT TYPE	Fuse



Powering Business Worldwide

Electrical rating

AMPERAGE RATING	3 A
INTERRUPT RATING	100 kAIC at 600 Vac 50 kAIC at 600 Vdc
VOLTAGE RATING	600 Vac, 600 Vdc

General information

CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Indicating

Physical details

MATERIAL	Melamine tube Nickel-plated bronze endcap
PACKAGING TYPE	Standard

Resources

CATALOGS	Bussmann series 2018 full line catalog no. 1007, section 2 - low voltage supplemental fuses
	KLM-3-LIMITRON FAST ACTING FUSE
	Bussmann series complete full line catalog no. 1007
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - KLM-3
TECHNICAL DATA SHEETS	Bussmann series KLM supplemental fuse data sheet No. 2020

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

