

Eaton 167693

Catalog Number: 167693

Eaton Moeller series xEffect - FRCmM-NA RCCB. FRCmM-NA-110, 2 pole, In: 25 A, Icn: 10 with back-up fuse kA, IΔN: 0.03 A, 110-V systems



General specifications

Product Name	Catalog Number
Eaton Moeller series xEffect - FRCmM-NA RCCB	167693
	Model Code
	FRCMM-25/2/003-G/A-NA-110
EAN	Product Length/Depth
4015081642359	80 mm
Product Height	Product Width
71 mm	35 mm
Product Weight	Compliances
0.22 kg	RoHS conform
Certifications	Catalog Notes
UL 1053	Additionally protects against special forms of residual pulsating DC which have not been smoothed.
IEC/EN 61008	
ÖVE E 8601	
EN45545-2	
IEC 61373	

Type

FRCmM-NA-110
Residual current circuit
breakers
Type G/A (ÖVE E 8601)

Special features

Current test marks as per
inscription
Maximum operating
temperature is 55 °C:
Starting at 40 °C, the max.
permissible continuous
current decreases by 3% for
every 1 °C
The maximum operating
current of back-up fuse must
not exceed the residual
current circuit breaker's
rated operational current

Application

Switchgear for 110-V systems

Amperage Rating

25 A

Features

Residual current circuit breaker
Additional equipment possible

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Application notes

[eaton-rcc-application-guide-br019003en-en-us.pdf](#)

Brochures

[UL 1053 DIN Rail RCCB](#)

Catalogs

[Eaton's Volume 4—Circuit Protection](#)

[eaton-xeffect-frcmm-na-rccb-catalog-ca003019en-en-us.pdf](#)

[eaton-xeffect-industrial-switchgear-range-catalog-ca003002en-en-us.pdf](#)

Certification reports

[DA-DC-03_FRCm](#)

Drawings

[eaton-circuit-breaker-xeffect-frcmm-na-rccb-dimensions.eps](#)

eCAD model

[ETN.FRCMM-25_2_003-G_A-NA-110.edz](#)

Installation instructions

[MA180503312](#)

mCAD model

[eaton-f9_ul1053_2p-3-d-model.stp](#)

[eaton-f9_ul1053_2p-drawing.dwg](#)

Specifications and datasheets

[Eaton Specification Sheet - 167693](#)

Wiring diagrams

[eaton-circuit-breaker-xeffect-frcmm-na-rccb-wiring-diagram.eps](#)

[eaton-xeffect-frcmm-rccb-wiring-diagram.jpg](#)

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Fitted with:

Interlocking device

Frame

45 mm

Frequency rating

50 Hz / 60 Hz

Pollution degree

2

Used with

FRCmM-NA-110

Residual current circuit breakers

Type G/A (ÖVE E 8601)

Mounting Method

Quick attachment with 2 latch positions for DIN-rail IEC/EN

60715

DIN rail

Climatic proofing

25-55 °C / 90-95% relative humidity according to IEC 60068-2

Equipment heat dissipation, current-dependent

2 W

Rated impulse withstand voltage (U_{imp})

4 kV

Rated short-time withstand current (I_{cw})

10 kA

Admissible back-up fuse overload - max

25 A gG/gL

Ambient humidity range

5 - 95 %

Built-in width (number of units)

35 mm (2 SU)

Short-circuit rating

Max. admissible back-up fuse: 63 A gG/gL, 70 A class J fuse

(UL)

Status indication

White / blue

Terminal protection

Finger and hand touch safe, DGUV VS3, EN 50274

Terminals (top and bottom)

Lift terminals

Test circuit range

100 V AC - 121 V AC, 94 V AC - 132 V AC (UL)

Ambient operating temperature - max

40 °C

Ambient operating temperature - min

-25 °C

Built-in depth

70.5 mm

Connectable conductor cross section (multi-wired) - max

16 mm²

Connectable conductor cross section (multi-wired) - min

1.5 mm²

Connectable conductor cross section (solid-core) - max

35 mm²

Connectable conductor cross section (solid-core) - min

1.5 mm²

Fault current rating

30 mA

Heat dissipation capacity

0 W

Heat dissipation per pole, current-dependent

1 W

Overvoltage tested - max

530 V

Permitted storage and transport temperature - max

60 °C

Permitted storage and transport temperature - min

-35 °C

Contact position indicator color

Red / green

Mounting position

As required

Lifespan, mechanical

10000 operations

Degree of protection

IP20

IP20, IP40 with suitable enclosure

Impulse withstand current

3 kA (8/20 μ s) surge-proof

Number of poles

Two-pole

Leakage current type

A

Lifespan, electrical

4000 operations

Functions

Short-time delayed tripping

Pick-up current

22 mA

Sensitivity type

Pulse-current sensitive

Terminal capacity (cable)

M5 (with cross-recessed screw as defined in EN ISO 4757-Z2, PZ2)

Rated fault current - max

0.03 A

Rated fault current - min

0.03 A

Rated insulation voltage (Ui)

440 V

Rated operational current for specified heat dissipation (In)

25 A

Rated operational voltage (Ue) - max

110 V

Rated residual making and breaking capacity

500 A

Static heat dissipation, non-current-dependent

0 W

Surge current capacity

3 kA

Width in number of modular spacings

2

Voltage rating (IEC/EN 60947-2)

110/190 V

Voltage rating (UL)

208/120 V, 60 Hz

Voltage type

AC

Terminal capacity (solid wire)

1.5 mm² - 35 mm²

Tripping time

10 ms delay at 50 Hz

8 ms delay at 60 Hz

Short time-delayed

Rated short-circuit strength

5 kA (UL, as per CSA)

10 kA with back-up fuse

Terminal capacity (stranded cable)

16 mm² (2x)

RAL-number

7035



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)