


Walraven BISOFIX® PIR50 + HD500

(D0386)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with HD500 clamp
- HD500 clamp with M8/M10 and M10/M12 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 110\text{mm}$ = 80kg/m^3
- PIR density for $D \geq 110\text{mm}$ = 120kg/m^3
- product is part of the Walraven Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range $-45\text{ }^{\circ}\text{C}$ - $+105\text{ }^{\circ}\text{C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Insulation Thickness Total Length		Maximum Allowed Load Faz
Reference letter	D	G	W x H x L	Is	Fa,z
Unit description	(mm)		(mm) x (mm) x (mm)	(mm)	(N)
I503304076	76.10	M10/M12	254 x 221 x 75	50	650
I503304089	88.90	M10/M12	274 x 240 x 75	50	690
I503304102	101.60	M10/M12	274 x 240 x 100	50	720
I503304108	108	M10/M12	290 x 256 x 100	50	760
I503304114	114.30	M10/M12	290 x 256 x 100	50	1680
I503304133	133	M10/M12	322 x 277 x 100	50	2780
I503304140	139.70	M10/M12	322 x 277 x 100	50	2860
I503304160	159 - 160	M10/M12	345 x 300 x 100	50	3090
I503304168	168.30	M10/M12	360 x 315 x 100	50	3200
I503304219	219.10	M10/M12	403 x 358 x 150	50	4810
I503304273	273.10	M10/M12	453 x 409 x 150	50	5620
I503304324	323.90	M10/M12	515 x 471 x 150	50	6390
I503304406	406.40	M10/M12	588 x 544 x 150	50	6410