


Walraven BISOFIX® PIR50 + 2S

(D0382)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 110\text{mm}$ = 80kg/m^3
- PIR density for $D \geq 110\text{mm}$ = 120kg/m^3
- clamp: zinc plated
- temperature range $-45\text{ }^{\circ}\text{C}$ - $+105\text{ }^{\circ}\text{C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Insulation Thickness Total Length		Maximum Allowed Load $F_{a,z}$
Reference letter	D	G	W x H x L	Is	$F_{a,z}$
Unit description	(mm)		(mm) x (mm) x (mm)	(mm)	(N)
I503303012	12	M8/M10	153 x 136 x 75	50	220
I503303015	15 - 16	M8/M10	153 x 136 x 75	50	250
I503303018	17.20 - 18	M8/M10	153 x 136 x 75	50	300
I503303020	20	M8/M10	168 x 151 x 75	50	340
I503303022	21.30 - 22	M8/M10	168 x 151 x 75	50	340
I503303025	25 - 26	M8/M10	168 x 151 x 75	50	350
I503303028	26.90 - 28	M8/M10	178 x 161 x 75	50	350
I503303032	32	M8/M10	178 x 161 x 75	50	370
I503303034	33.70 - 35	M8/M10	178 x 161 x 75	50	370
I503303040	40	M8/M10	185 x 168 x 75	50	440
I503303042	42.40	M8/M10	185 x 168 x 75	50	470
I503303048	48.30	M8/M10	194 x 177 x 75	50	500
I503303050	50	M8/M10	194 x 177 x 75	50	510
I503303054	54	M8/M10	203 x 186 x 75	50	520
I503303057	56 - 57	M8/M10	203 x 186 x 75	50	520
I503303060	60.30	M8/M10	203 x 186 x 75	50	540
I503303064	64	M8/M10	217 x 199 x 75	50	550
I503303070	70	M8/M10	217 x 199 x 75	50	600
I503303076	76.10	M8/M10	227 x 210 x 75	50	650
I503303089	88.90	M8/M10	239 x 221 x 75	50	690
I503303102	101.60	M8/M10	249 x 232 x 100	50	720
I503303108	108	M8/M10	260 x 243 x 100	50	760
I503303114	114.30	M8/M10	260 x 243 x 100	50	1680