


Walraven BISOFIX® PIR30 + 2S

(D0362)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D \leq 110\text{mm}$ = 80kg/m^3
- PIR density for $D > 110\text{mm}$ = 120kg/m^3
- clamp: zinc plated
- temperature range -45°C - $+105^\circ\text{C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Insulation Thickness Total Length		Maximum Allowed Load $F_{a,z}$
Reference letter	D	G	W x H x L	Is	$F_{a,z}$
Unit description	(mm)		(mm) x (mm) x (mm)	(mm)	(N)
I303303012	12	M8/M10	118 x 103 x 75	30	130
I303303015	15 - 16	M8/M10	118 x 103 x 75	30	170
I303303018	17.20 - 18	M8/M10	118 x 103 x 75	30	190
I303303020	20	M8/M10	118 x 103 x 75	30	200
I303303022	21.30 - 22	M8/M10	124 x 109 x 75	30	230
I303303025	25	M8/M10	124 x 109 x 75	30	260
I303303028	26.90 - 28	M8/M10	136 x 119 x 75	30	300
I303303032	32	M8/M10	136 x 119 x 75	30	310
I303303034	33.70 - 35	M8/M10	136 x 119 x 75	30	320
I303303040	40	M8/M10	143 x 127 x 75	30	340
I303303042	42.40	M8/M10	143 x 127 x 75	30	350
I303303048	48.30	M8/M10	153 x 136 x 75	30	370
I303303050	50	M8/M10	153 x 136 x 75	30	370
I303303054	54	M8/M10	153 x 136 x 75	30	380
I303303057	56 - 57	M8/M10	153 x 136 x 75	30	390
I303303060	60.30	M8/M10	168 x 151 x 75	30	410
I303303064	64	M8/M10	168 x 151 x 75	30	420
I303303070	70	M8/M10	178 x 161 x 75	30	440
I303303076	76.10	M8/M10	178 x 161 x 75	30	460
I303303089	88.90	M8/M10	194 x 177 x 75	30	500
I303303102	101.60	M8/M10	203 x 186 x 100	30	550
I303303108	108	M8/M10	217 x 199 x 100	30	620
I303303114	114.30	M8/M10	227 x 210 x 100	30	1370
I303303133	133	M8/M10	239 x 221 x 100	30	1520
I303303140	139.70	M8/M10	249 x 232 x 100	30	1570
I303303160	159 - 160	M8/M10	271 x 253 x 100	30	1720