

Product data sheet

Item No. 92.257.1004.1

Cable assembly GST1815K1-S 15 10SW

geis® Connection cable male - free end; length: 1m; type GST1815; 5-pole; 250/400 V / 16 A; colour of coding: black with black strain-relief; cable: H05VV-F 5G1,5, colour: black



Item No.	92.257.1004.1
EAN	4015573588066
Order Unit	30 Piece(s)

Certificates / Approvals



Technical data

**General**

Rated current	16 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

**Model**

Number of poles	5
Nominal cross section conductor	1.5 mm <sup>2</sup>
Degree of protection (IP)	IP40
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F



Cable colour	Black
Cable diameter	10.1 mm
Version of cable	Male - free end
Type of cord set	Connection cable
Version cable end 1	GST18i5 plug
Version cable end 2	Free end

**Material**

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

**Dimensions**

Total length	1 m
--------------	-----

**Technical drawing**

Kabel/cable H05VV-F 5G 1,5  
Farbe/colour: siehe Tabelle/see table

Stecker/Male connector

Gesamtlänge/total length L ± 3%

Typ/type: GST18i5KS-S 15 .. SW = schwarz/black  
WS = weiß/white

.F	Farbe colour	Codierung *Y* <small>check meta</small>	Kabelfarbe cable colour
.1	schwarz black	1 2 PE N 3	schwarz black
.2	weiß white		weiß white

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.257.XX04.F	XX in dm-Schritten	92.257.1004.1 = 10dm/L= 1000mm	GST18i5KS-S 15 10SW
U2.257.XX04.F	XX in m-Schritten	U2.257.1204.1 = 12 m/L=12000mm	GST18i5KS-S 15 X12SW

Freitoleranz nach General tolerance (M) - drawing, no manual modifications allowed

Zeichnung Nr./Drawing No. 92.257.0504.1 01K g

Wieland Wieland Electric

PRE-ASSEMBLED CABLE KONFEKT-LEITUNG  
Stecker/mate - freies Ende/free end  
Schraubanschluß/screw connection 250V/400V 1,5mm

01-PEM-08/91