


Walraven BISOFIX® PIR20 + 2S

(D0352)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D \leq 110\text{mm}$ = 80kg/m^3
- PIR density for $D > 110\text{mm}$ = 120kg/m^3
- clamp: zinc plated
- temperature range -45°C - $+105^\circ\text{C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Insulation Thickness Total Length		Maximum Allowed Load $F_{a,z}$
Reference letter	D	G	W x H x L	Is	$F_{a,z}$
Unit description	(mm)		(mm) x (mm) x (mm)	(mm)	(N)
I203303012	12	M8/M10	84 x 74 x 75	20	120
I203303015	15 - 16	M8/M10	93 x 83 x 75	20	160
I203303018	17.20 - 18	M8/M10	93 x 83 x 75	20	170
I203303020	20	M8/M10	93 x 83 x 75	20	180
I203303022	21.30 - 22	M8/M10	93 x 83 x 75	20	180
I203303025	25	M8/M10	99 x 89 x 75	20	190
I203303028	26.90 - 28	M8/M10	99 x 89 x 75	20	200
I203303032	32	M8/M10	111 x 96 x 75	20	210
I203303034	33.70 - 35	M8/M10	111 x 96 x 75	20	220
I203303040	40	M8/M10	118 x 103 x 75	20	260
I203303042	42.40	M8/M10	124 x 109 x 75	20	280
I203303048	48.30	M8/M10	136 x 119 x 75	20	300
I203303050	50	M8/M10	136 x 119 x 75	20	310
I203303054	54	M8/M10	136 x 119 x 75	20	320
I203303057	56 - 57	M8/M10	143 x 127 x 75	20	330
I203303060	60.30	M8/M10	143 x 127 x 75	20	340
I203303064	64	M8/M10	153 x 136 x 75	20	350
I203303070	70	M8/M10	153 x 136 x 75	20	370
I203303076	76.10	M8/M10	153 x 136 x 75	20	390
I203303089	88.90	M8/M10	178 x 161 x 75	20	430
I203303102	101.60	M8/M10	185 x 168 x 100	20	450
I203303108	108	M8/M10	194 x 177 x 100	20	500
I203303114	114.30	M8/M10	203 x 186 x 100	20	1110
I203303133	133	M8/M10	227 x 210 x 100	20	1360
I203303140	139.70	M8/M10	227 x 210 x 100	20	1410
I203303160	159 - 160	M8/M10	249 x 232 x 100	20	1520
I203303168	168.30	M8/M10	260 x 243 x 100	20	1570