



Description AFFD MINIATURE CIRCUIT BREAKER

Code AFDD

No. of poles 1P+N

No. modules 2


Rated current 16 A

Curve C

Rated voltage 230 V

Standard	IEC EN 62606; IEC EN 60898-1	Rated frequency (f)	50/60 Hz
Breaking capacity EN 60898 230V (Icn)	6000 A	Breaking capacity IEC/EN 60947-2 (Ics)	6 kA
Breaking capacity IEC/EN 60947-2 230/240V (Icu)	7,5 kA	Rated impulse withstand voltage (Uimp)	4 kV
Insulation voltage (Ui)	500 V	Overvoltage protection threshold	275 V ac
Minimum operating voltage	170 V ac	Can be accessorized	No
Electrical endurance	10.000	Mechanical endurance	20.000
Section rigid cable	25 mm ²	Section flexible cable	25 mm ²
Rated tightening torque	2,8 Nm	Operating temperature	-25 + 55°C (With temperatures greater than 30°C, derating of In rated current is expected)
Stocking temperature	-40°C + +70°C		

DIMENSIONAL



STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and
coordination of Polifin S.p.A.

www.gewiss.com
sat@gewiss.com
Last update 21/04/2026

Data, measures, designs and pictures are shown
only as informative purposes,
and could be changed without previous notice