

Walraven BISOFIX® E32 + Bifix® G2

(D0342)

for insulated pipes



Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with Bifix® G2 clamp
- Bifix® G2 with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 80\text{mm}$ = 80kg/m^3
- PIR density for $D \geq 80\text{mm}$ = 120kg/m^3
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range $-45\text{ }^{\circ}\text{C}$ - $+105\text{ }^{\circ}\text{C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Insulation Thickness Total Length		Maximum Allowed Load $F_{a,z}$
Reference letter	D	G	W x H x L	Is	$F_{a,z}$
Unit description	(mm)		(mm) x (mm) x (mm)	(mm)	(N)
I323008012	12	M8/M10	118 x 100 x 50	32.30	100
I323008015	15	M8/M10	125 x 107 x 50	32.50	100
I323008018	17.20 - 18	M8/M10	125 x 107 x 50	32.30	100
I323008022	21.30 - 22	M8/M10	134 x 115 x 50	33	100
I323008028	27 - 28	M8/M10	148 x 129 x 50	36	100
I323008035	33.70 - 35	M8/M10	148 x 129 x 50	32.50	100
I323008042	42.40	M8/M10	155 x 137 x 50	32.80	150
I323008048	48.30	M8/M10	155 x 137 x 50	32.30	225
I323008054	54	M8/M10	172 x 154 x 50	35.30	225
I323008060	60.30	M8/M10	172 x 154 x 50	32.30	350
I323008064	64	M8/M10	201 x 183 x 50	44	350
I323008070	70	M8/M10	201 x 183 x 50	41	425
I323008076	76.10	M8/M10	201 x 183 x 50	40.30	575
I323008089	88.90	M8/M10	229 x 208 x 50	43.60	875
I323008102	102	M8/M10	248 x 227 x 50	45.20	100
I323008108	108	M8/M10	248 x 227 x 50	42	1075
I323008114	114	M8/M10	248 x 227 x 50	40.30	1250
I323008133	133	M8/M10	275 x 253 x 100	42.70	1475
I323008140	140	M8/M10	275 x 253 x 100	40.30	1700