

Walraven BISOFIX® E19 + HD500

(D0320)

for insulated pipes



Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with HD500 clamp
- HD500 clamp with M8/M10 and M10/M12 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 80\text{mm}$ = 80kg/m^3
- PIR density for $D \geq 80\text{mm}$ = 120kg/m^3
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range $-45\text{ }^{\circ}\text{C}$ - $+105\text{ }^{\circ}\text{C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Insulation Thickness Total Length		Maximum Allowed Load $F_{a,z}$
Reference letter	D	G	W x H x L	Is	$F_{a,z}$
Unit description	(mm)		(mm) x (mm) x (mm)	(mm)	(N)
I193304076	76.10	M10/M12	193 x 170 x 50	25.30	575
I193304089	88.90	M10/M12	200 x 177 x 50	25.30	875
I193304102	101.60	M10/M12	215 x 191 x 50	25.30	1000
I193304108	108	M10/M12	240 x 207 x 50	25.30	1075
I193304114	114.30	M10/M12	240 x 207 x 50	25.30	1250
I193304133	133	M10/M12	274 x 240 x 100	26.20	1475
I193304140	139.70	M10/M12	274 x 240 x 100	25.30	1700
I193304160	159 - 160	M10/M12	290 x 256 x 100	25.30	1950
I193304168	168.30	M10/M12	290 x 256 x 100	25.30	2125
I193304219	219.10	M16	360 x 315 x 100	25.30	3525
I193304273	273.10	M16	403 x 358 x 100	25.30	3525