



Color: ■ gray

#### Mounting accessories WINSTA® IDC

The mounting accessories from the WINSTA® IDC product line is the intelligent solution for trouble-free installation. You can rely on the level of quality of WINSTA® components from WAGO for your electrical installation accessories too.

Lower costs through fast commissioning and elimination of service expenses – solutions from WINSTA® IDC

WINSTA® is the pluggable connection system that is optimally tailored to the strict requirements of electrical installation. It ensures error-free installation of cables and components, quickly and reliably. Now you can also lower installation expenses without compromising quality and safety: with protection against mismatching reduces the need for servicing and prevents unnecessary downtime.

- products perfectly tailored to your requirements guarantee safe use
- quick replacement of defective units during ongoing operation

#### Notes

General safety information

#### **NOTICE: Observe installation and safety instructions!**

- Nur von Elektrofachkraft oder einer für die Tätigkeit elektrisch unterwiesenen Person (EUP nach DIN VDE 0105-100) anzuwenden!
- Nicht unter Spannung/Last installieren!
- Nur für bestimmungsgemäßen Gebrauch einsetzen!
- Nationale Vorschriften/Normen/Richtlinien beachten!
- Technische Daten der Produkte beachten!
- Auf die richtige Polbelegung achten!
- Keine beschädigten/verschmutzten Komponenten verwenden!
- Leiterarten, -querschnitte, Abisolierlängen und Leitungsdurchmesser beachten!
- Leiter bis zum Anschlag einführen!
- Nur mit Verriegelungsklinke und Zugentlastung verwenden!
- Originalzubehör verwenden!

**To be sold only with installation instructions!**

### Mechanical data

Mounting type	Screw mount
Suitable	for flat cable 5 x 2.5 mm <sup>2</sup> , 5 x 4 mm <sup>2</sup> , 5 x 2.5 mm <sup>2</sup> + 2 x 1.5 mm <sup>2</sup>

### Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	gray
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.108 MJ
Weight	3.7 g

### Environmental requirements

Processing temperature	-5 ... +40 °C
Continuous operating temperature	-35 ... +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

### Commercial data

Product Group	20 (Winsta)
PU (SPU)	100 pcs
Packaging type	Box
Country of origin	CH
GTIN	4045454205126
Customs tariff number	39269097900

### Product Classification

UNSPSC	39121703
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 9.0	EC000127
ETIM 10.0	EC000127
ECCN	NO US CLASSIFICATION

### Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

### Downloads

#### Environmental Product Compliance

##### Compliance Search

Environmental Product  
Compliance 897-878



## Documentation

### Bid Text

897-878	19.02.2019	xml 2.57 KB	
897-878	09.01.2015	doc 22.50 KB	

## CAD/CAE-Data

### CAE data

WSCAD Universe 897-878	
---------------------------	---