

Sylbay 4000K L2 9000LM AISLE SSCS
0040371



Features

- Logistics and Industry modular high bay luminaire with aisle optics to provide necessary illumination for narrow areas. Single body with 2 optical modules, 9100 lumens, 57W, 160lm/W, 4000K, CRI 80, aisle beam optic, 3 step MacAdam ellipse, grey finish (RAL7012), Class 1, 220-240V, IP65, IK08 (Sensor IK03), (LxWxH) 410x386x133mm, Mains + control cable of 2 meter. SylSmart Standalone enabled.


Product Overview

Product name	Sylbay 4000K L2 9000LM AISLE SSCS
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
Fixture luminous flux (lm)	9100
Luminaire efficacy (lm/W)	160
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Beam Angle (°)	30*60
Glare control	< 19
Photobiological Risk Group	RG1
Total power consumption (W)	57
Electrical protection	Class I
Control gear type	Electronic ballast
Control gear mounting	Integral


Sylbay 4000K L2 9000LM AISLE SSCS
0040371

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288403717
Warranty	5 years

Photometry



Technical drawings



Data table

GENERAL DATA

Product name	Sylbay 4000K L2 9000LM AISLE SSCS
--------------	-----------------------------------

Sylbay 4000K L2 9000LM AISLE SSCS 0040371

Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	9100
Luminaire efficacy (lm/W)	160
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Beam Angle (°)	30*60
Glare control	< 19
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	57
Primary Supply/Product voltage - min (V)	220
Lamp power factor	0.98
Electrical protection	Class I
Control gear required	No
Control gear type	Electronic ballast
Control gear mounting	Integral
Drive current (mA)	400
Inrush Current (A)	65
Inrush Duration (µs)	268

Sylbay 4000K L2 9000LM AISLE SSCS 0040371

Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	5
Max. products per 20A B Breaker	6

LIFETIME DATA

Lifespan L70 B50	120000
Lifespan L70 B20	120000
Lifespan L70 B10	120000
Lifespan L80 B50	120000
Lifespan L80 B20	120000
Lifespan L80 B10	100000
Lifespan L90 B50	71500
Lifespan L90 B20	58000
Lifespan L90 B10	52000

PHYSICAL DATA

Housing colour	Grey
IP rating	IP65
IK rating	IK08
IK rating of sensor	IK03
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	410
Nominal Product Width (mm)	386
Weight (kg)	5.17

PACKAGING

Single packaging type	Carton
Product EAN number	5410288403717
Packaging single width (cm)	48.0
Packaging single depth (cm)	26.0
DUN14 (outer)	05410288403717



Sylbay 4000K L2 9000LM AISLE SSCS
0040371

Packaging outer length / height (cm)	60.0
--------------------------------------	------

SAFETY DATA

Optimal operating condition (°C)	-20-40
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No