Specifications





Eaton 9PX2000RT

Eaton 9PX UPS, 2U, 2000 VA, 1800 W, 5-20P input, Outputs: (6) 5-20R, (1) L5-20R, 120V

General specification	ns
PRODUCT NAME	Eaton 9PX UPS
CATALOG NUMBER	9PX2000RT
UPC	743172081278
PRODUCT LENGTH/DEPTH	23.8 in
PRODUCT HEIGHT	3.4 in
PRODUCT WIDTH	17.3 in
PRODUCT WEIGHT	61.5 lb
WARRANTY	3 year limited
COMPLIANCES	IEC 62040-2 Cat C1 CISPR22 Class B FCC part 15 Class B VCCI Class B
CERTIFICATIONS	cULus Listed NOM ENERGY STAR certified ICC-ES AC156 OSHPD Seismic certified
GLOBAL CATALOG	9PX2000RT



Battery	
BATTERY MANAGEMENT	ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)
BATTERY REPLACEMENT	Hot-swappable internal batteries and extended battery modules (EBMs)
BATTERY TYPE	Sealed, lead-acid
EXTENDED BATTERY CAPABILITY	Add up to 4 extended battery modules (EBM). Part number 9PXEBM72RT

ne/Double-conversion W VA e sine wave
0 W
0 VA
e sine wave
V
V default 0/110/120/125V)
steady-state
50 Hz

Electrical input	
INPUT CONNECTION	<u>5-20P</u>
INPUT CORD LENGTH	8 ft
INPUT NOMINAL VOLTAGE	120V default (100/110/120/125V)
INPUT FREQUENCY RANGE	60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz
INPUT POWER FACTOR	>0.99 typical

Communications	
COMMUNICATION	MiniSlot + 1 USB port + 1 serial RS232 port + 1 mini- terminal block for remote ON/OFF + 1 mini-terminal block for remote power off + 1 mini-terminal block for output relay Communication slot
EXPANSION SLOTS	 (1) Mini-Slot (MS) expansion port. The following optional connectivity cards may be ordered separately. Gigabit Network Card part number: NETWORK-M3 Modbus card part number: INDGW- M2 Relay card part number: RELAY-MS
SOFTWARE COMPATIBILITY	Intelligent Power Software Suite
USER INTERFACE	Graphical display, 5-button programmable menu

Environmental	
ALTITUDE	0-1500m (0° to 40°C), 1500-3000m (0° to 35°C)
BTU RATING	Online: 578, Battery: 974
NOISE LEVEL	<47 dB at 1 meter
RELATIVE HUMIDITY	0-96% non-condensing
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)

Additional specificat	tions
FORM FACTOR	Rack/tower
RACK SIZE	2U
RACK MOUNTING KIT	Yes
EFFICIENCY AT MAX. LOAD	91
PACKAGE CONTENTS	 9PX2000RT UPS 4-post rail kit Safety manual User manual Tower pedestals RS-232 serial cable USB cable Intelligent Power Software Suite CD
INTERNAL BYPASS	Yes

Warranty and support	
STANDARD FACTORY WARRANTY	 3-YEAR FACTORY WARRANTY - 3 years - Parts, electronics and batteries coverage - Standard ground shipping - Technical support
EXTENDED SERVICE PLANS	 ADVANCED DEPOT EXCHANGE - 5-year depot repair: 9SW5Y-2200UC - Expedited parts coverage for 5 years - Parts, electronics and UPS batteries coverage - Next business day shipping - Technical support 5-YEAR ON-SITE PLAN: WFLN75XX-2509UC - On-site parts and labor coverage for years 5 - Parts, electronics and UPS batteries coverage - 24x7 on-site labor coverage, next-day response - Next-day shipping - Technical support

Resources	
	Eaton 9PX 700-3000 VA UPS brochure
BROCHURES	Eaton UPS Services Quick Guide - EN
	Eaton UPS and battery services - EN
	Eaton 9PX UPS 2000-3000 VA 120V outline drawing
DRAWINGS	Battery Integration System Pro-E drawing
	Eaton 9PX UPS 2000RT technical drawing
	9PX 700-3000 VA 2U UPS user guide
MANUALS AND USER GUIDES	9PX battery integration system user guide
	9PX 2-post rack kit user guide
	Eaton 9PX UPS guide specification: 700-3000 VA
SPECIFICATIONS AND DATASHEETS	9PX 700-3000 VA UPS technical specification
	<u>Eaton Specification Sheet - 9PX2000RT</u>

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

 $\hbox{@ 2025 Eaton.}$ All Rights Reserved.

Follow us on social media to get the latest product and support information.









