

## Data Sheet | Item Number: 709-170

Disconnect lock; for disconnect tab used on 280/281 and 769 Series disconnect terminal blocks; red

<https://www.wago.com/709-170>



Color: ■ red

### Material data

Note (material data)	<a href="https://www.wago.com/us/material-specifications">Information on material specifications can be found here</a>
Color	red
Fire load	0.023 MJ
Weight	0.8 g

### Commercial data

Product Group	2 (Terminal Block Accessories)
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 8.0	EC002848
ETIM 7.0	EC002848
PU (SPU)	200 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4017332812412
Customs tariff number	39269097900

### Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

## Downloads

### Environmental Product Compliance

#### Compliance Search

Environmental Product Compliance 709-170



## Documentation

### Additional Information

Technical Section

pdf  
2240.62 KB



### Bid Text

709-170

19.02.2019

xml  
2.55 KB



709-170

28.04.2017

doc  
23.00 KB



## CAD/CAE-Data

### CAD data

2D/3D Models 709-170




### CAE data

WSCAD Universe 709-170



## Installation Notes



### Double Safety:

The disconnect tab has been designed for maximum operational safety.

As soon as the disconnect tab is in the disconnect position, it can be protected against unintentional reconnection by using the disconnect lock.

Only through intentional and deliberate use of a tool, can the disconnect lock be removed and the circuit reconnected.

### Features/Benefits:

- Easy to use
- Install/remove disconnect lock with just one hand
- Clearly identify disconnect tab position
- Higher safety
- Intentional effort is required to re-connect the circuit

Installation



Installing a disconnect lock on the terminal block's disconnect tab.



Unlocking a disconnect lock.



Removing a disconnect lock.