

Data Sheet | Item Number: 206-1216

Variocrimp 16 crimping tool; for insulated and uninsulated ferrules; Crimping range: 6, 10 and 16 mm²

<https://www.wago.com/206-1216>



Color: green/black



Notes

Note

Application Notes

- Select the wire gauge on "Variocrimp 16" before crimping.
- Only one crimping station is needed to handle the specified conductor range.
- Uniform, compact crimping all four sides for high conductor retention.
- No need to center the ferrules into the terminals.
- Crimping can be performed from either side (for left- or right-handed users).
- Built-in ratchet mechanism ensures gas-tight crimp connection.
- Crimping tools open automatically after crimping operation is complete.
- Ergonomically designed handles.

What is a "gas-tight" connection?

In a gas-tight connection, the conductor and the ferrule are compressed, eliminating all spaces. Under normal atmospheric conditions, neither a liquid nor gaseous medium can penetrate the crimped connection.

Oxidation between crimped single conductors is prevented, virtually eliminating the possibility of any increase in the crimped connection's resistance. In some exceptional cases, minute, isolated spaces may be present. However, these instances can be considered as closed off due to the twisted conductor.

Inadequate crimping can allow the conductor to be pulled out of the connection. Hollow spaces also remain, permitting oxidation formation and an increase in contact resistance.

Elevated resistance is detrimental for both signal transmission (signal flow is damped) and power transmission, resulting in power loss and contact heating (risk of fire).

Crimping tools with built-in ratchets are recommended (e.g., **WAGO Crimping Tools**). These tools open automatically after the crimping operation is complete. Space-saving crimping from all four sides is ideal for spring clamp termination.

Ferruled conductor cross-sections specified for WAGO products are based on this crimping method.

Physical data

Width	75 mm / 2.953 inches
Height	207 mm / 8.15 inches
Depth	26 mm / 1.024 inches

Mechanical data

Conductor Entry	Side
Automatic conductor cross-section adjustment	No
Crimp shape	Square crimp
Crimping pressure, adjustable	No
Locking mechanism, releasable	Yes

Material data

Color	green/black
Fire load	0 MJ
Weight	600 g

Commercial data

PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4066966853322
Customs tariff number	8203200000

Product Classification


UNSPSC	27112147
ETIM 9.0	EC000168
ETIM 10.0	EC000168
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search
Environmental Product Compliance 206-1216 

1 Compatible Products

1.1 Optional Accessories


1.1.1 Tool

1.1.1.1 Crimping tool



Item No.: 206-1206
Spring clamp; small; for 206-1204 and 206-1216

Installation Notes



Insert the ferruled conductor into the crimping station.



Squeeze handles until ratchet mechanism is released.



Only for "Variocrimp 16":
Adjust conductor cross-section with crimping tool in open position.

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com