

GIOTTO 335 4000K RECESSED
3034794



Features

- Ambient and decorative round, recessed mounted LED bulkhead luminaire. White robust polycarbonate body with opal diffuser, 2350lm, 18.2W, 129lm/W, 4000K, CRI 80, non-dimmable, 120,000 hours lumen maintenance (L70:B50). Drive current: 600mA, IP44, IK10, Class I, 220-240V.


Product Overview

Product name	GIOTTO 335 4000K RECESSED
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
Environment	Indoor
E-number FI	4270228
Fixture luminous flux (lm)	2350
Luminaire efficacy (lm/W)	129
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 26
Photobiological Risk Group	RG0
Total power consumption (W)	18.2
Electrical protection	Class I
Control gear type	LED driver constant current
Control gear mounting	Integrated
LED Flickering Rate	Ultra low (5% or less)
Housing colour	White


GIOTTO 335 4000K RECESSED
3034794

IP rating	IP44
IK rating	IK10
Product EAN number	8711971347941
Warranty	5 years
Colour Code	840

Photometry



Technical drawings



Data table

GENERAL DATA

GIOTTO 335 4000K RECESSED 3034794

Product name	GIOTTO 335 4000K RECESSED
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
Environment	Indoor
Operating temperature range (°C)	-25°C...+25°C
Performance ambient temperature Tq (°C)	25
E-number FI	4270228
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	2350
Luminaire efficacy (lm/W)	129
Colour temperature (K)	4000
Colour Code	840
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Adjustable chromaticity	N
Glare control	< 26
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	80

ELECTRICAL DATA

Total power consumption (W)	18.2
Primary Supply/Product voltage - min (V)	220
Lamp power factor	0.92
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Control gear mounting	Integrated

GIOTTO 335 4000K RECESSED 3034794

Drive current (mA)	600
Inrush Current (A)	40
Inrush Duration (µs)	400
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	52
Max. products per 20A B Breaker	62
Connectable conductor cross section - Min (mm²)	0.75
Connectable conductor cross section - Max (mm²)	2.5

LIFETIME DATA

Lifespan L70 B50	170000
Lifespan L80 B10	127500
Lifespan L90 B10	61500

PHYSICAL DATA

Housing colour	White
IP rating	IP44
IK rating	IK10
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Diameter (mm)	355
Weight (kg)	1.2
Recessed Depth (mm)	41

PACKAGING

Single packaging type	Carton
Product EAN number	8711971347941
Packaging single width (cm)	35.7

**GIOTTO 335 4000K RECESSED
3034794**

Packaging single depth (cm)	10.6
DUN14 (outer)	08711971347941
Packaging outer length / height (cm)	35.7

SAFETY DATA

Optimal operating condition (°C)	-25-25
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No