



Color: white

Similar to illustration



Dimensions in mm

- 1) Diameter of drilled hole: 4.2 mm
- 2) Diameter of drilled hole: 5.2 mm

### Conductor support, 267 Series, white

Enjoy fault-free electrical installations with conductor support (item number 267-435). The white housing is made of polyamide (PA66) for insulation, the clamping spring is made of chrome-nickel spring steel (CrNi), and the contacts are made of electrolytic copper (ECu). The contact surface is coated with tin.

#### Electrical data

Ratings per		IEC/EN 60664-1		
Overvoltage category	III	III	II	
Pollution degree	3	2	2	
Nominal voltage	-	500 V	-	
Rated surge voltage	-	4 kV	-	
Rated current	-	6 A	-	

#### Connection data

Number of connection types	1
----------------------------	---

#### Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	white
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Clamping spring material	Chrome-nickel spring steel (CrNi)
Contact material	Electrolytic copper (E <sub>Cu</sub> )
Contact Plating	Tin
Fire load	0.258 MJ
Weight	10.6 g

## Environmental requirements

Temperature stability	105 °C
-----------------------	--------

## Commercial data

Product Group	8 (Misc. Chassis Mount Blocks)
eCl@ss 10.0	27-44-03-14
eCl@ss 9.0	27-44-03-14
ETIM 9.0	EC002560
ETIM 8.0	EC000458
PU (SPU)	50 pcs
Packaging type	Box
Country of origin	PL
GTIN	4044918997829
Customs tariff number	85369010000

## Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

## Approvals / Certificates

### General approvals



Approval	Standard	Certificate Name
CCA DEKRA Certification B.V.	EN 61984	NL-47718
KEMA/KEUR DEKRA Certification B.V.	EN 61984	71-100641
UL UL International Germany GmbH	UL 1977	E45171

## Downloads

### Environmental Product Compliance

#### Compliance Search

Environmental Product  
Compliance 267-435



## Documentation

### Additional Information

Technical Section	03.04.2019	pdf 2027.26 KB
-------------------	------------	-------------------



CAD/CAE-Data

CAD data

2D/3D Models 267-435



CAE data

ZUKEN Portal 267-435

