



Short description:

WAGO's RS-232/SMI interface module offers a standard interface to SMI-compliant electrical drives. The interface represents a purely physical level conversion between the standard RS-232 interface and the SMI signal level. The interface module operates up to 16 SMI drives. The entire SMI range of functions can be used. The special WAGO-I/O-PRO function blocks communicate between applications and SMI drives. These function blocks support both single and group addressing, as well as status monitoring. The SMI Interface Module can be used with RS-232 onboard interfaces from 750 Series Programmable Fieldbus Controllers and with the serial 750-650/003-000 or 753-650/003-000 RS-232 Interface. The module must be supplied with an external 24 VDC power source. The 24 V power supply and RS-232 connectors are electrically isolated from the SMI connectors. There is no electrical isolation between power supply and RS-232. The module is DIN-35-rail mountable.

Notes on SMI:

SMI stands for "Standard Motor Interface," a standard interface for electrical drives. SMI was developed to connect drives with integrated electronic circuitry for applications in shutters and sunshade systems.

Electrical data

Nominal operating voltage	24 VDC
Operating voltage range	±10 %
Current consumption at nominal supply voltage	≤ 55 mA (inside)
Number of SMI channels	1
Number of drives per channel	16
Status indicator	Green LED
Interface	RS-232 (interface input)
Specialty functions	SMI

Safety and protection

Protection type	IP20
-----------------	------

Connection Data

Cable length (max.)	350 m (SMI bus; ≤ 3 m for data and power supply cable, RS-232)	Connection 1	
		Connection technology	CAGE CLAMP®
		WAGO connector	WAGO 804 Series
		Solid conductor	0.5 ... 2.5 mm ² / 20 ... 12 AWG
		Fine-stranded conductor	0.5 ... 2.5 mm ² / 20 ... 12 AWG
		Strip length	10 ... 11 mm / 0.39 ... 0.43 inches

Physical data

Width	35 mm / 1.378 inches
Height	90 mm / 3.543 inches
Depth from upper-edge of DIN-rail	55 mm / 2.165 inches

Mechanical data

Mounting type	DIN-35 rail
Mounting position	any
Housing design	DIN-rail-mount enclosure

Material data

Fire load	0 MJ
Weight	80 g

Environmental requirements

Ambient temperature (operation)	0 ... +50 °C
Ambient temperature (storage)	-25 ... +85 °C

Standards and Specifications

Standards/specifications	EN 50090-2-2
--------------------------	--------------

Commercial data

Product Group	6 (INTERFACE ELECTRONIC)
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4050821100317
Customs tariff number	85389099990

Product Classification

UNSPSC	32151705
eCl@ss 10.0	27-37-12-16
eCl@ss 9.0	27-37-12-16
ETIM 9.0	EC000225
ETIM 10.0	EC000225
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
EAC GZO Almaty Standart	TP TC 020/2011	EAC CoC 03083

Downloads

Environmental Product Compliance

Compliance Search
Environmental Product Compliance 789-912

Documentation

Bid Text			
789-912	19.02.2019	xml 5.77 KB	
789-912	20.11.2014	doc 27.00 KB	

CAD/CAE-Data

CAE data	
EPLAN Data Portal 789-912	
WSCAD Universe 789-912	

1 Compatible Products

1.1 Optional Accessories

1.1.1 Ferrule

1.1.1.1 Ferrule



Item No.: 216-241
 Ferrule; Sleeve for 0.5 mm² / 20 AWG; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; white

Item No.: 216-242
 Ferrule; Sleeve for 0.75 mm² / 18 AWG; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; gray

Item No.: 216-243
 Ferrule; Sleeve for 1 mm² / AWG 18; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; red

Item No.: 216-244
 Ferrule; Sleeve for 1.5 mm² / AWG 16; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; black

1.1.2 Jumper

1.1.2.1 Jumper



Item No.: 789-112

Jumper; 12-way; silver-colored

1.1.3 Marking

1.1.3.1 Marker



Item No.: 2009-145

Mini-WSB In-line; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white



Item No.: 248-502

Mini-WSB marking card; as card; MARKED; 1 ... 10 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 248-566

Mini-WSB marking card; as card; MARKED; 1 ... 50 (2x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 248-503

Mini-WSB marking card; as card; MARKED; 11 ... 20 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 248-504

Mini-WSB marking card; as card; MARKED; 21 ... 30 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 248-506

Mini-WSB marking card; as card; MARKED; 41 ... 50 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 248-452

Mini-WSB marking card; as card; MARKED; K (100x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 248-450

Mini-WSB marking card; as card; MARKED; K1 - K10 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 248-451

Mini-WSB marking card; as card; MARKED; K11 - K20 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 248-455

Mini-WSB marking card; as card; MARKED; U 100 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 248-453

Mini-WSB marking card; as card; MARKED; U1, ... U10 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 248-454

Mini-WSB marking card; as card; MARKED; U11 - U20 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 248-501

Mini-WSB marking card; as card; not stretchable; plain; snap-on type; white

1.1.3.2 Marking device



Item No.: 210-110

Fiber-tip pen

1.1.4 Tool

1.1.4.1 Operating tool



Item No.: 210-720

Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured