Global Trac Electrical Accessories

GLOBAL TRAC PRO L FEED OUT WHITE

XTS35-3

Product features

- Global Trac Pro accessory - white, glass fibre reinforced polycarbonate L-feed that is applicable for three-circuit track systems where the polarity ridge is in the outer side. Dimensions - 99 x 99 x 33 mm (L x W x H).

PRODUCT OVERVIEW

Product name	GLOBAL TRAC PRO L FEED OUT WHITE
Technology	Accessory
Housing	PC Polycarbonate
General application	Retail
ETIM Class	EC002556
E-number SE	7402230
Warranty	5 years
Light colour	N/A
Dimmable	No
Housing colour	RAL 9010 - Pure white
IP rating	IP20
IK rating	IK02
Product EAN number	6410014507350

DATA TABLE

General data

Product name	GLOBAL TRAC PRO L FEED OUT WHITE
Technology	Accessory
Housing	PC Polycarbonate
General application	Retail
Operating temperature range (°C)	0°C...+25°C
ETIM Class	EC002556
E-number SE	7402230
Warranty	5 years

Optical data

Light colour	N/A

Electrical data

© Feilo Sylvania | Date Printed: 06 Feb 2024

Global Trac Electrical Accessories

GLOBAL TRAC PRO L FEED OUT WHITE

XTS35-3

Dimmable	No

Physical data

Housing colour	RAL 9010 - Pure white
IP rating	IP20
IK rating	IK02
Nominal Product Length (mm)	99
Nominal Product Width (mm)	99
Nominal Product Height (mm)	33
Weight (kg)	0.097

Packaging

Single packaging type	Plastic
Product EAN number	6410014507350
Packaging single length / height (cm)	13.4
Packaging single width (cm)	23.3
Packaging single depth (cm)	3.2
DUN14 (outer)	06410014507350
Units per outer package	25
Packaging outer length / height (cm)	19.3
Packaging outer width (cm)	39.6
Packaging outer depth (cm)	12.0

Safety data

Optimal operating condition (°C)	0-25
Special purpose lamp	No
Dry applications use only	Yes

TECHNICAL DRAWINGS



© Feilo Sylvania | Date Printed: 06 Feb 2024