

29P-1612-CS: Press-fitt adapter to copper pipe 16x12 CW724



This press fitting extended with a piece of copper pipe (50mm) is the perfect solution to switch from an existing installation in copper to a Henco solution with multiple connections.

Commercial information

Basic unit dimensions

Height	22 mm
Length	92 mm
Width	22 mm
Net weight	0.061 kg

Certificates

ATG, DVGW Wasser, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, QB (CSTBat), AFNOR, ACS, PZH, DNV-GL, Sans 21003, Kontrol Biro, EMI

Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Material quality connection 1	CuZn21Si3P (CW724R)	Outer pipe diameter connection 1	16 Millimetre
Surface protection connection 1	Untreated	Outer pipe diameter connection 2	12 Millimetre
Surface treatment connection 1	Untreated	Length	92 Millimetre
Material connection 2	Copper	Length of connection 1	30 Millimetre
Material quality connection 2	Dezincification resistant brass (DZR)	Working length connection 1	30 Millimetre
Surface protection connection 2	Untreated	Length of connection 2	50 Millimetre
Surface treatment connection 2	Untreated	Working length connection 2	50 Millimetre
Shape	Straight	Wrench width	0 Millimetre
Reducing	✗	Wrench width union nut	0 Millimetre
Eccentric	✗	Tightening torque	0 0 Newtonmetre
System specific	✓	Medium temperature (continuous)	-10 70 Degrees celsius
Connection 1	Press sleeve	Max. operating pressure at 20 °C	16 Bar
Contour code connection 1	TH	Max. operating pressure at max. medium temperature	10 Bar
Connection 2	Soldered end	Standard Dimension Ratio (SDR)	0
Contour code connection 2	V		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✗		
High tensile strength	✗		
With thermal insulation	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✗		
Capped	✗		
With connection indicator	✗		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✓		
KIWA certified	✓		
Gastec QA mark	✗		
KOMO certified	✓		
Type approval according to BBR/EKS	✗		