


Walraven RapidRail® Fixing Rail

(G0406)

channels for light-duty applications



Features & benefits

- C-profile
- for quick and adjustable fixing of one or multiple pipes
- with continuous perforation
- distance between rail end and first hole is always equal
- with sawing marks each 50 mm
- flexible hole pattern with anchor holes and also small holes to use wood screws
- unique hole pattern at rail 30x20 allows to click in Walraven RapidRail® Hammerfix from both sides
- special hole pattern and material thickness for 32x20 rail
- material: steel 1.0242
- pre-galvanized
- for more information about the max. allowed load (Faz) please refer to the loading tables or our online datasheet 'Technical Details Walraven RapidRail®'

EPD



Product Number	Type	Total Width x Total Height x Total Length	Material Thickness	Profile Opening
Reference letter		W x H x L	MT	S
Unit description		mm x mm x mm	mm	mm
650527182	27x18	27 x 18 x 2,000	1.00	15
650527183	27x18	27 x 18 x 3,000	1.00	15
650527184	27x18	27 x 18 x 4,000	1.00	15
650527186	27x18	27 x 18 x 6,000	1.00	15
650530150	30x15	30 x 15 x 500	1.50	15
650530152	30x15	30 x 15 x 2,000	1.50	15
650530153	30x15	30 x 15 x 3,000	1.50	15
650530156	30x15	30 x 15 x 6,000	1.50	15
650530202	30x20	30 x 20 x 2,000	1.25	15
650530203	30x20	30 x 20 x 3,000	1.25	15
650530206	30x20	30 x 20 x 6,000	1.25	15
650530302	30x30	30 x 30 x 2,000	1.50	15
650530303	30x30	30 x 30 x 3,000	1.50	15
650530306	30x30	30 x 30 x 6,000	1.50	15