

P-PIPESTOP32: Stop end for pipe Press Ø32



Commercial information

These fittings offer great advantages with regard to corrosion.

- The body of the fitting consists of brass CW617N.
- The fitting is equipped with a thrust ring to prevent direct galvanic contact between the aluminium of the pipe and the brass of the fitting.
- Electrolysis is thus excluded.
- The fitting is equipped with EPDM O-rings and stainless steel press sleeves with 3 control windows.
- To prevent assembly errors, the stainless steel press sleeves are marked with the size and type of press profile that can be pressed.

Certificates

ATG, DVGW Wasser, ETA, ÖVGW Wasser, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, SABS, EMI

Applications

Potable water, Heating, Compressed air, Cooling, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material connection 1	Brass	Outer pipe diameter connection 1	32 Millimetre
Material quality connection 1	CuZn40Pb2 (CW617N)	Max. operating pressure at 20 °C	10 Bar
Surface protection connection 1	Untreated	Wrench width	0 Millimetre
Surface treatment connection 1	Untreated	Wrench width union nut	0 Millimetre
System specific	✓	Standard Dimension Ratio (SDR)	0
Nominal diameter connection 1	DN 20		
Connection 1	Press sleeve		
Contour code	BE		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
With drain valve	✗		
With de-aerator	✗		
Capped	✗		
FM quality mark	✗		
UL quality mark	✗		
ULC quality mark	✗		
LPCB quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✗		
KIWA certified	✗		
Gastec QA mark	✗		
KOMO certified	✗		
Type approval according to BBR/EKS	✗		

Related products