


UFH-0605MDK04-PRM-BV: 4-groups man. comp,flow meter 0-3L,therm.,washer and air vent 4x + 2 b



Commercial information

Preassembled composite manifold for both residential and non-residential construction. The compact structure of this manifold and its adjustable brackets allow for easy installation. This manifold comes with flow meters and a calibration system per group, as well as with a fill and drain valve and manual vent. The outlet connections are 3/4" eurocone.

These plastic manifolds offer the following advantages:

- Preassembled: simply mount and connect
- Suitable for heating and cooling
- Compact structure
- Suitable for PN6 installations
- Cooling without condensation
- Ball valves UFH-BM0606-VN are included

Basic unit dimensions

| | |
|------------|----------|
| Height | 335 mm |
| Length | 318 mm |
| Width | 99 mm |
| Net weight | 2.495 kg |

Certificates

Applications

Heating, Cooling, Underfloor Heating

Solutions

Building installations, Underfloor heating, Industry, Utility

Technical characteristics

| | | | |
|---------------------------------------|--|--|----------------------|
| Connection type primary side | 2-pipe | Outer pipe diameter primary connection | 32 Millimetre |
| Suitable for cooling | ✓ | Medium temperature (continuous) | 0 60 Degrees celsius |
| Material | Plastic | Max. operating pressure | 6 Bar |
| Position primary connection | Left/right | Max. number of expansion groups | 15 |
| Primary connection | Internal thread cylindrical BSPT-Rp (ISO 7-1 / EN 10226-1) | Number of groups secondary | 4 |
| Nominal diameter primary connection | 1 inch (25) | Outer pipe diameter secondary | 12 20 Millimetre |
| With valves on primary connection | ✗ | Flow-through capacity | 0 5 Litre per hour |
| With mixing valve | ✗ | Min. pressure difference secondary flow/return | 0 Kilo Pascal |
| Expandable | ✓ | Width | 99 Millimetre |
| Multi-zone manifold | ✗ | Height | 335 Millimetre |
| With temperature limit | ✗ | Depth | 318 Millimetre |
| With non-return valve | ✗ | | |
| With circulation pump | ✗ | | |
| Article compression class | PN 6 | | |
| With controller | ✗ | | |
| Hydraulic balance control | None | | |
| Volume flow measurement | Analogue | | |
| With thermometer | ✓ | | |
| Temperature measurement supply | Analogue | | |
| Temperature measurement return | Analogue | | |
| With de-aeration | ✓ | | |
| With pressure gauge | ✗ | | |
| Secondary connection | Euroconus standardless | | |
| Nominal diameter secondary connection | 3/4 inch (20) | | |
| Closable groups | ✓ | | |
| With flow-through indicator | ✓ | | |
| With thermal actuator | ✗ | | |
| With wall-mounting bracket | ✓ | | |
| With casing | ✗ | | |