### Data Sheet | Item Number: 267-164


Female connector; without ground contact; with snap-in mounting feet; 4-pole; 1,00

mm<sup>2</sup>; white

https://www.wago.com/267-164







Similar to illustration

1) Diameter of drilled hole: 4.2 mm 2) Diameter of drilled hole: 5.2 mm

Female connector, 267 Series, white

Effortless electrical installations are guaranteed with this female connector (item number 267-164). Strip lengths must be 8 mm when connecting conductors to this female connector. This product features one conductor terminal and utilizes PUSH WIRE®. Our proven PUSH WIRE® connection offers the fastest method for clamping conductors. It utilizes the conductor's stiffness to overcome the clamping spring's contact force. The clamping spring is made of chrome-nickel spring steel (CrNi), the contacts are made of electrolytic copper (ECu), and the white housing is made of polyamide (PA66) for insulation. The contact surface is coated with tin.

Electrical data				
Ratings per	IE	EC/EN 60664-	1	
Overvoltage category	III	III	II	
Pollution degree	3	2	2	
Nominal voltage	-	500 V	-	
Rated surge voltage	-	4 kV	-	
Rated current	-	6 A	-	

Connection data			
Number of connection types	1	Connection 1	
		Connection technology	PUSH WIRE®
		Strip length	8 mm / 0.31 inches
		Pole number	4

Physical data		
Width	26 mm / 1.024 inches	
Height from the surface	34 mm / 1.339 inches	
Depth	42 mm / 1.654 inches	

# Data Sheet | Item Number: 267-164

https://www.wago.com/267-164



Material data	
Note (material data)	la farmation and material and altitude in the farmation
	<u>Information on material specifications can be found here</u>
Color	white
Material group	
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	VO
Clamping spring material	Chrome-nickel spring steel (CrNi)
Contact material	Electrolytic copper (E <sub>Cu</sub> )
Contact Plating	Tin
Fire load	0.316 MJ
Weight	8.4 g

#### **Environmental requirements**

Temperature stability 105 °C

Commercial data	
Product Group	8 (Misc. Chassis Mount Blocks)
eCl@ss 10.0	27-44-03-14
eCl@ss 9.0	27-44-03-14
ETIM 9.0	EC002560
ETIM 8.0	EC000458
PU (SPU)	500 pcs
Packaging type	Bag
Country of origin	PL
GTIN	4044918499682
Customs tariff number	85366990990

#### **Environmental Product Compliance**

Compliant, No Exemption RoHS Compliance Status

### Approvals / Certificates

#### General approvals







Approval	Standard	Certificate Name
CCA DEKRA Certification B.V.	EN 61984	NL-47718
KEMA/KEUR DEKRA Certification B.V.	EN 61984	71-100641
UL UL International Germany GmbH	UL 1977	E45171
VDE VDE Prüf- und Zertifizie- rungsinstitut	EN 61984	40032309


## Data Sheet | Item Number: 267-164

https://www.wago.com/267-164









Subject to changes. Please also observe the further product documentation!

Page 3/3 Version 13.02.2025