Walraven RapidRail® Connector 90° (L/L)

(G3508)

to make Walraven RapidRail® fabrications



Features & benefits

- connector with pre-assembled Walraven RapidRail® Slide nut(s)
- to make rail fabrications
- suitable for rails 27x18, 30x15, 30x20, 30x30, 30x45, 38x40
- ready-to-use pre-assembled for a quick fixing, and retains assembly in place before final tightening
- material: metal parts made of steel 1.0332; spring(s) made of POM (polyoxymethylene), green
- zinc plated
- For detailed technical information about our RAL marked products, please see the RAL datasheet in our web catalogue.

Product Number	For Rail Type	Angle	Total Width x Total Height x Total Length	Material Thickness	Width	Fixing Hole	Fixing Slot	Heart To Heart Distance	Torque Moment For Installation	Maximum Allowed Load Faz	Maximum Allowed Load Fax
Reference letter		*a*	*W x H x L*	*MT*	*w*	*FH*	*FS*	*k*	*T inst.*	*Fa,z*	*Fa,x*
Unit description		*°*	*mm x mm x mm*	*mm*	*mm*	*mm*	*mm*	*mm*	*Nm*	*N*	*N*
6584011	27x18, 30x15, 30x20, 30x30, 30x45, 38x40	90	30 x 103.5 x 93.5	3.00	30	8.2	12x4	50	15	1,562	720