

Obico 80

OBICO 80 IP65 820LM 2CCT 930/940 DIM WHT

0005366



Product features

- Integrated LED recessed spotlight, 2-axis adjustable (horizontal rotation 360°, vertical tilt 30°) RAL9016 white bezel colour, two temperature light colors selectable: 3000K, 4000K. Lumen output 820lm (4000K), 8.2W, dimmable trailing/leading edge, 38° degree beam angle, aluminium and steel body, low profile 40mm recessed depth, IP65 frontal degree, IK07, loop-in/loop-out terminals for fast wiring, 80mm cutout, clear lens. Air-proof, to limit air leakage when used in residential applications within the building's thermal envelope. Directly coverable with insulation material according to EN60598-1







PRODUCT OVERVIEW

Product name	OBICO 80 IP65 820LM 2CCT 930/940 DIM WHT
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Residential & Consumer, Retail
ETIM Class	EC001744
E-number FI	4278508
Warranty	5 years
Useful luminous flux (Fuse)	820
Fixture luminous flux (lm)	820
Luminaire efficacy (lm/W)	100
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM4
Beam Angle (°)	38
Glare control	< 25
Photobiological Risk Group	RG1
Total power consumption (W)	8.2
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP65/20
IK rating	IK07
Product EAN number	5410288053660

PHOTOMETRY

Obico 80 OBICO 80 IP65 820LM 2CCT 930/940 DIM WHT 0005366



TECHNICAL DRAWINGS

