# walraven

## Walraven Pacifyre® EFC Fire Collar

### *(U0425)*

The flexible soloution for simple to complex situations with plastic and multi-layer pipes





#### Features & benefits

- Simple and easy to install, without special training
- Only one box for numerous penetrations and all pipe dimensions (Ø ≤ 160 mm)
- High flexibility due to close wall distance
- Suitable for difficult to access penetrations
- Zero distance between fire collars is possible
- Expansion and contraction of the pipe remains possible
- Suitable for damp conditions
- Contains no dangerous materials
- The required length of the stainless steel and intumescent strip can be determined on the job site
- Only the exact amount of intumescent band is required: minimal use of material per penetration
- Left-over material can be attached to another Walraven Pacifyre<sup>®</sup> EFC fire collar
- Max. 3 pipes through 1 fire collar (Ø ≤ 75 mm) when space in between is ≤ 15 mm
- Fire safe tested up to EI 120 U/U
- Tested and approved according to EN 1366-

Product Number Outside Pipe Diameter

#### Total Width x Total Height x Total Depth

| Reference letter |          | W×H×DtT            |
|------------------|----------|--------------------|
| Unit description | (mm)     | (mm) x (mm) x (mm) |
| 2132100600       | 16 - 175 | 392 x 215 x 295    |
| 2132100700       | 32 - 160 | 40 × 2 × 10000     |