

Product datasheet

Specifications



Distribution Block, Linergy FC, for compact NSX250 4P fixed W/O Connection

LVS04408

EAN Code: 3606481870681

Price: 711,00 EUR

Main

Range	Linergy
Range of product	Linergy
Product or component type	Device feeder
Product name	Linergy FC
Accessory / separate part category	Connection accessory
Range compatibility	PrismaSeT PrismaSeT P cubicle

Complementary

installation description	Cubicle - width 650 mm
Number of devices	3 (4P)
Poles description	4P

Rates duty January 2016

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Installed device	ComPact: fixed NSX100...160 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX250 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX100...160 with earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX250 with earth leakage protection - control: toggle - vertical installation ComPact: fixed INS250 - control: direct front rotary handle - vertical installation ComPact: fixed INV250 - control: direct front rotary handle - vertical installation ComPact: fixed NSX100...160 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: fixed NSX250 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: fixed NSX100...160 without earth leakage protection - control: motor mechanism - vertical installation ComPact: fixed NSX250 without earth leakage protection - control: motor mechanism - vertical installation ComPact: plug-in NSX100...160 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX250 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX100...160 without earth leakage protection - control: motor mechanism - vertical installation ComPact: plug-in NSX250 without earth leakage protection - control: motor mechanism - vertical installation ComPact: plug-in NSX100...160 without earth leakage protection - control: toggle - vertical installation ComPact: plug-in NSX250 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX100...160 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: fixed NSX250 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: fixed NSX100...160 with earth leakage protection - control: motor mechanism - vertical installation ComPact: fixed NSX250 with earth leakage protection - control: motor mechanism - vertical installation ComPact: plug-in NSX100...160 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX250 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX100...160 with earth leakage protection - control: motor mechanism - vertical installation ComPact: plug-in NSX250 with earth leakage protection - control: motor mechanism - vertical installation ComPact: plug-in NSX100...160 with earth leakage protection - control: toggle - vertical installation ComPact: plug-in NSX250 with earth leakage protection - control: toggle - vertical installation
Mounting support	Mounting plate
Installation direction	Horizontal
[Ui] rated insulation voltage	750 V AC
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	675 A at 40 °C
[Ue] rated operational voltage	690 V
[Ipk] rated peak withstand current	50 kA
I²t on activation	25000000 A².s
Permissible current	675 A at 40 °C 615 A at 60 °C 570 A at 70 °C
Connections - terminals	Outgoer: plug in (phase / neutral) , 3 outgoers
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASTA KEMA

Quantity per set	Set of 1
Length	440 mm
Height	132 mm
Depth	235 mm
Net weight	8 kg
Colour	Black

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.0 cm
Package 1 Width	24.5 cm
Package 1 Length	46.0 cm
Package 1 Weight	4.488 kg
Unit Type of Package 2	P12
Number of Units in Package 2	42
Package 2 Height	103.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	200.0 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
REACH Regulation	REACH Declaration
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes

Use Again

Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	Yes
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins