
Walraven RapidStrut® U-Connector linear (BUP1000)

(H28103)

for linear rail connections





Features & benefits

- U-shaped for extra stability
- longitudinal connector for all Walraven RapidStrut® rails
- for strong connections and in combination with Double Walraven RapidStrut® rails it is advised to use linear connectors on both sides of the rail
- the hole pattern is adapted to the hole pattern of Walraven RapidStrut*rails to use throughbolts
- material: steel 1.0242 (S250GD) + ZM310 MAC
- product is part of the Walraven Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227

Product Number	For Rail Type	Total Width x Total Height x Total Length	Material Thickness	Width	Fixing Hole	Torque Moment For Installation	Maximum Allowed Load Fax
Reference letter		WxHxL	MT	w	FH	Tinst.	Fa,x
Unit description		mm x mm x mm	mm	mm	mm	Nm	N
66588121	41x21, 41x41, 41x51, 41x62, 41x82	50 x 21.5 x 175	4.00	42	12.2	25	1,870
66588141	41x21, 41x41, 41x51, 41x62, 41x82	50 x 41.5 x 175	4.00	42	12.2	25	2,280