

220-042 40W 3300K specific configuration
Post top light | silver | 12/20/30/40W | 2700K/3300K/4000K

Introduction

Purpose of this Document

This document provides information for 220-042 40W 3300K. During measurement, the product is used in a different mode where output power, colour temperature and/or beam angle are changed from factory standard. These adjustments can be made without altering the product and are designed to be set by the installer. In most cases, the options are set through switches on the product.

Results

Total input power	38.9 W
Correlated Colour Temperature	3445 K
Total lumen output	3288 lm
Efficiency	84 lm/W

Electrical measurement details

Input Power


RMS Input voltage feed. V_{RMS}	228 V
RMS Input current feed. I_{RMS}	0.178 A
Total input power	38.9 W

Frequency of input power	50 Hz
Power factor	0.96
Displacement power factor	0.97

Total harmonic distortion of the current	15.05%
Total harmonic distortion of the voltage	2.68%

Input Power Curve

Voltage - Current



Efficiency

Radiated power efficiency: 24.4%




Lumen efficiency: 84 lm/W



Harmonics

3rd Harmonic	12.24%
5th Harmonic	5.42%
7th Harmonic	3.26%
9th Harmonic	4.25%
11th Harmonic	1.75%

Current Harmonics %




220-042 40W 3300K specific configuration

Colour measurement details


Total lumen output 3288 lm
 Correlated Colour Temperature 3445 K
 Colour coordinates CIE 1931 (x;y) = (0.406;0.386)
 Colour deviation from BBL Duv = -0.0024

TM30-18 Colour Fidelity Index R_f 75.4
 TM30-18 Colour Gamut Index R_g 94.2
 Colour Rendering Index (Ra) CRI 73.7
 Colour Rendering Index. (red component) R_9 = -25.8


Colour Quality Scale CQS = 72.2
 Television Lighting Consistency Index TLCI = 48




Relative spectral power distribution



TM30 details




TM30 Colour vectors per hue bin




TM30 Colour distortion


Hue Bin	R_f	Shifts (%)	
		Chroma	Hue
C1	72	-17%	-1%
C2	71	-13%	11%
C3	62	-4%	19%
C4	76	3%	15%
C5	86	7%	8%
C6	86	7%	-4%
C7	83	-3%	-11%
C8	85	-8%	-5%
C9	81	-12%	4%
C10	67	-13%	18%
C11	65	-1%	24%
C12	72	8%	13%
C13	85	9%	0%
C14	77	12%	-13%
C15	74	0%	-19%
C16	72	-8%	-16%



TM30-18 R_f -values per reference colour




TM30-18 R_f -values per hue bin




TM30 Chroma shift

Colour Quality details



Colour Rendering Index



Colour Quality Scale