

Gel straight-through joint
with connection block

Universally suitable for connecting all polymeric cables and conductors (e.g. N(A)YY, NYM, H05), cross section range from 1.5 mm² to 6 mm². Suitable for aluminium and copper conductors.



Product description

Article name	EASYCELL 5 V+
Article number	486520
Copyright	EASYCELL is a registered trademark of BBC Cellpack GmbH


Characteristics

- Connector area completely sealed by gel
- Re-accessible and ready for immediate operation
- New snap closing system (IP68), no cable ties required
- High-quality shockproof plastic shells, flame retardant and UV-resistant
- Quick, safe and easy assembly

Applications

- Indoor
- Outdoor
- Cable ducts

Technical Data



Article name	EASYCELL 5 V+
Article number	486520
Voltage levels	U0/U (Um) 0,6/1 (1,2) kV
Test standards	DIN EN IEC VDE 60670-1
Selection Note	6 - 16 mm ²
Housing type	5
Number of housing	1 Pieces
Connector type	Connection block
Number of connector	5 Pieces
Length L	183 mm
Width B	72 mm
Height H	42 mm
Nominal cross section Polymeric cable unarmoured per conductor 3x min	6 mm ²
Nominal cross section Polymeric cable unarmoured per conductor 3x max	16 mm ²
Nominal cross section Polymeric cable unarmoured per conductor 4x min	6 mm ²
Nominal cross section Polymeric cable unarmoured per conductor 4x max	16 mm ²
Nominal cross section Polymeric cable unarmoured per conductor 5x min	6 mm ²
Nominal cross section Polymeric cable unarmoured per conductor 5x max	16 mm ²
Diameter cable min	14 mm
Diameter cable max	22 mm
Conductor material	Copper
IP protection class	IP68
IP protection class (associated standard)	IEC 60529
Housing colour	black
Housing material	Polypropylene
Closure type	Latching
Wiring direction	Two-sided
Gel Material	Silicone gel
Voltage range	1000 V
Voltage range (associated standard)	IEC 60670-1
Flammability class housing	V2

Flammability class housing (associated standard)	IEC 60695-2-11
Rated surge voltage	3 kV
Rated surge voltage (associated standard)	IEC 60670-1
Operating temperature range max	90 °C
Operating temperature range (associated standard)	IEC 60670-1
Mounting temperature min	-10 °C
Mounting temperature max	60 °C
Dielectric strength	27 kV/mm

Commercial Data

Article name	EASYCELL 5 V+
Article number	486520
Delivery scope	Gel straight-through joint
	Connection block
	Allen key
	Installation instruction
Shelf life description	Unlimited shelf life
Storage temperatur max	40 °C
Storage temperatur min	0 °C
Country of origin	Italy
Customs tariff number	85369010
EAN/GTIN	4010311212616

Packaging data

Packaging type	Carton	Pallet
Content quantity	6	360
Unit of measure	Piece	Piece
Lenght (mm)	250	1200
Width (mm)	210	800
Height (mm)	180	1020
Net weight (kg)	4.5	270
Gross weight (kg)	4.8	288.2