

PIXO LINE 1500 ASYM R 840 WHITE
0007836



Features

• Pixo Line is a linear track system, adds flexibility to any space due the variety of product optionsOffers an easy installation with two separate modulesPush-in/push-out mechanism with GR6d-15 connectorCompatible with Zhaga Book 14Aluminium body, plastic end caps,traslucent asymmetric optic diffuser, light beam angle:25° white finishing colour.Light color temperature: 4000K, max. system power: 50WMax. fixture lumen output: 7400lm, efficacy: 148lm/W, Ra80 typical, LED chromacity: 3 step MacAdam ellipse (SDCM3), IR/UV free light source without heat radiationMultipower driver module with 8 power settings meet all installation needs with one single product, selection and setting on driver - between 17W (350mA), 19W (400mA), 24W (500mA), 29W (600mA), 34W (700mA), 38W (800mA), 43W (900mA), 50W (1050mA)Suitable for installation on 3-circuit tracks, please check compatibility list on the instruction sheet. Compatible with OneTrackElectrical protection: Class III. Degree of protection: IP20, suitable for indoor environment onlyLight modules should be combined with suitable in-track driversNominal product dimensions: L.1464mmx38.4mmx37mm


Product Overview

Product name	PIXO LINE 1500 ASYM R 840 WHITE
Technology	LED
Cap/Base	N/A
Mount	Track mounting
General application	Hospitality, Museums & Galleries, Office, Retail
ETIM Class	EC000996
Fixture luminous flux (lm)	7400
Luminaire efficacy (lm/W)	148
Correlated colour temperature (k)	4000

PIXO LINE 1500 ASYM R 840 WHITE
0007836

Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	90
Beam Angle (°)	Single assymetric 25right
Photobiological Risk Group	Not applicable
Total power consumption (W)	50
Electrical protection	Class III
Dimmable	No
Housing colour	White
IP rating	IP20
IK rating	IK03
Product EAN number	5410288078366
Warranty	5 years
Dimming method	N/A
Useful luminous flux (#use)	7400

Photometry



Technical drawings

