

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture  
Product name : COLORJELT  
Product code : NITRO AEROSOL  
Type of product : Aerosol,Paints  
Vaporizer : Aerosol

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial  
For professional use only

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

ESSEM  
ZA du Vernais  
F-38780 Eyzin Pinet - France  
T +33(0)4.74.58.40.80  
[renard@itwpc.com](mailto:renard@itwpc.com)

### 1.4. Emergency telephone number

Emergency number : 04.74.58.40.80

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229  
Serious eye damage/eye irritation, Category 2 H319  
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336  
Full text of H-statements: see section 16

#### Adverse physicochemical, human health and environmental effects

No additional information available

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Contains :

Acetone

Hazard statements (CLP) :

H222 - Extremely flammable aerosol.  
H229 - Pressurised container: May burst if heated.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.

# COLORJELT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

P211 - Do not spray on an open flame or other ignition source.  
P251 - Do not pierce or burn, even after use.  
P261 - Avoid breathing spray.  
P271 - Use only outdoors or in a well-ventilated area.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.  
EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dimethyl ether	CAS-No.: 115-10-6 EC-No.: 204-065-8 EC Index-No.: 603-019-00-8 REACH-no: 01-2119472128-37	20 – 40	Flam. Gas 1A, H220 Press. Gas
Acetone	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-49	10 – 30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
n-butyl acetate	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	10 - 20	Flam. Liq. 3, H226 STOT SE 3, H336
2-methoxy-1-methylethyl acetate	CAS-No.: 108-65-6 EC-No.: 203-603-9 REACH-no: 01-2119475791-29	< 10	Flam. Liq. 3, H226 STOT SE 3, H336
Hydrocarbon-solvents (Aromatic)	CAS-No.: 64742-95-6 EC-No.: 265-199-0 REACH-no: 01-2119455851-35	< 5	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
xylene	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32	< 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg de poids corporel) Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

# COLORJELT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve	CAS-No.: 111-76-2 EC-No.: 203-905-0 EC Index-No.: 603-014-00-0	< 5	Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg de poids corporel) Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg de poids corporel) Eye Irrit. 2, H319 Skin Irrit. 2, H315
4-methylpentan-2-one; isobutyl methyl ketone	CAS-No.: 108-10-1 EC-No.: 203-550-1 EC Index-No.: 606-004-00-4	< 5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 STOT SE 3, H335

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest. Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Repeated exposure may cause skin dryness or cracking.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after eye contact	: Causes serious eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

No additional information available

### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

# COLORJELT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapours/spray.

Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. On land, sweep or shovel into suitable containers. Collect spillage. Minimise generation of dust. Store away from other materials.

#### 6.4. Reference to other sections

See Section 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash hands, forearms and face thoroughly after handling.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Keep container tightly closed.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1. National occupational exposure and biological limit values

###### dimethyl ether (115-10-6)

###### France - Occupational Exposure Limits

Local name	Oxyde de diméthyle
VME (OEL TWA)	1920 mg/m <sup>3</sup>
VME (OEL TWA) [ppm]	1000 ppm

# COLORJELT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

<b>Acetone (67-64-1)</b>	
<b>France - Occupational Exposure Limits</b>	
Local name	Acétone
VME (OEL TWA)	1210 mg/m <sup>3</sup>
VME (OEL TWA) [ppm]	500 ppm
VLE (OEL C/STEL)	2420 mg/m <sup>3</sup>
VLE (OEL C/STEL) [ppm]	1000 ppm
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
<b>France - Occupational Exposure Limits</b>	
Local name	Acétate de 2-méthoxy-1-méthyléthyle
VME (OEL TWA)	275 mg/m <sup>3</sup>
VME (OEL TWA) [ppm]	50 ppm
VLE (OEL C/STEL)	550 mg/m <sup>3</sup>
VLE (OEL C/STEL) [ppm]	100 ppm
<b>xylene (1330-20-7)</b>	
<b>France - Occupational Exposure Limits</b>	
Local name	Xylène, isomères mixtes, purs
VME (OEL TWA)	221 mg/m <sup>3</sup>
VME (OEL TWA) [ppm]	50 ppm
VLE (OEL C/STEL)	442 mg/m <sup>3</sup>
VLE (OEL C/STEL) [ppm]	100 ppm
<b>n-butyl acetate (123-86-4)</b>	
<b>France - Occupational Exposure Limits</b>	
Local name	Acétate de n-butyle
VME (OEL TWA)	710 mg/m <sup>3</sup>
VME (OEL TWA) [ppm]	150 ppm
VLE (OEL C/STEL)	940 mg/m <sup>3</sup>
VLE (OEL C/STEL) [ppm]	200 ppm
<b>4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)</b>	
<b>France - Occupational Exposure Limits</b>	
Local name	Méthylisobutylcétone
VME (OEL TWA)	83 mg/m <sup>3</sup>
VME (OEL TWA) [ppm]	20 ppm
VLE (OEL C/STEL)	208 mg/m <sup>3</sup>
VLE (OEL C/STEL) [ppm]	50 ppm

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

# COLORJELT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

No additional information available

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Avoid all unnecessary exposure.

#### 8.2.2.1. Eye and face protection

##### Eye protection:

Chemical goggles or safety glasses

#### 8.2.2.2. Skin protection

##### Hand protection:

Time of penetration is to be checked with the glove producer. Chemical resistant gloves (according to European standard NF EN 374 or equivalent). The choice of appropriate gloves depends not only on the material, but also on other quality criteria that may vary from one manufacturer to another. As the product is a preparation made from several substances, glove material resistance may not be calculated in advance and must be tested before use. The exact penetration time of glove material is to be determined by the manufacturer of protective gloves and respected.

##### Other skin protection

##### Materials for protective clothing:

Wear suitable protective clothing

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. In case of inadequate ventilation wear respiratory protection.

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Other information:

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Characteristic.
Odour	: Organic solvent.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: < 0 °C
Flammability	: Extremely flammable aerosol.
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: < 0 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not applicable.
Viscosity, kinematic	: Not available

# COLORJELT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Solubility	: soluble in most organic solvents.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 0.976 g/l
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 90.4744

#### 9.2.2. Other safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Not established.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### dimethyl ether (115-10-6)

LC50 Inhalation - Rat	312 mg/l/4h
-----------------------	-------------

#### Acetone (67-64-1)

LD50 oral rat	5800 mg/kg
---------------	------------

# COLORJELT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

<b>Acetone (67-64-1)</b>	
LD50 dermal rabbit	> 15800 mg/kg
LC50 Inhalation - Rat	≈ 76 mg/l/4h
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat	23.8 mg/l /6H
LC50 Inhalation - Rat [ppm]	4345 ppm /6H
<b>n-butyl acetate (123-86-4)</b>	
LD50 oral rat	10760 mg/kg
LD50 dermal rabbit	> 14112 mg/kg
LC50 Inhalation - Rat	23.4 mg/l/4h
Skin corrosion/irritation	: Not classified pH: Not applicable.
Additional information	: Based on available data, the classification criteria are not met Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not applicable.
Additional information	: Based on available data, the classification criteria are not met
Respiratory or skin sensitisation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
<b>Acetone (67-64-1)</b>	
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)
STOT-single exposure	: May cause drowsiness or dizziness.
Additional information	: Based on available data, the classification criteria are not met
<b>Acetone (67-64-1)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>Hydrocarbon-solvents (Aromatic) (64742-95-6)</b>	
STOT-single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.
<b>n-butyl acetate (123-86-4)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)</b>	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met

# COLORJELT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

<b>xylene (1330-20-7)</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified  
Additional information : Based on available data, the classification criteria are not met

<b>COLORJELT</b>	
Vaporizer	Aerosol

### 11.2. Information on other hazards

#### 11.2.1. Endocrine disrupting properties

#### 11.2.2. Other information

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

## SECTION 12: Ecological information

### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

<b>dimethyl ether (115-10-6)</b>	
LC50 - Fish [1]	> 4000 mg/l
EC50 - Crustacea [1]	> 4000 mg/l

<b>Acetone (67-64-1)</b>	
LC50 - Fish [1]	5540 – 11000 mg/l
EC50 - Crustacea [1]	8800 mg/l
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic algae	430 mg/l

<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
LC50 - Fish [1]	> 100 mg/l
EC50 - Crustacea [1]	> 500 mg/l
ErC50 algae	> 1000 mg/l

<b>n-butyl acetate (123-86-4)</b>	
LC50 - Fish [1]	18 mg/l
EC50 - Crustacea [1]	44 mg/l
EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
ErC50 algae	647.7 mg/l
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic algae	200 mg/l

# COLORJELT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 12.2. Persistence and degradability

#### COLORJELT

Persistence and degradability	Not established.
-------------------------------	------------------

### 12.3. Bioaccumulative potential

#### COLORJELT

Bioaccumulative potential	Not established.
---------------------------	------------------

#### dimethyl ether (115-10-6)

Partition coefficient n-octanol/water (Log Pow)	0.18
---	------

#### Acetone (67-64-1)

Partition coefficient n-octanol/water (Log Kow)	-0.24
---	-------

#### 2-methoxy-1-methylethyl acetate (108-65-6)

Partition coefficient n-octanol/water (Log Pow)	0.36
---	------

Partition coefficient n-octanol/water (Log Kow)	0.43
---	------

#### n-butyl acetate (123-86-4)

Partition coefficient n-octanol/water (Log Kow)	2.3
---	-----

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

Additional information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information






In accordance with ADR / IMDG / IATA / ADN / RID /

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
<b>14.2. UN proper shipping name</b>				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS

# COLORJELT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
<b>Transport document description</b>				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
<b>14.3. Transport hazard class(es)</b>				
2.1	2.1	2.1	2.1	2.1
				
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

#### Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

#### Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

# COLORJELT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

### Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

#### 15.1.2. National regulations

France	
Occupational diseases	
Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

# COLORJELT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Press. Gas	Gases under pressure
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet (SDS), EU

# COLORJELT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

---

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.