



Color: ■ orange

Material data

Color	orange
Insulation material	Polycarbonate (PC)
Flammability class per UL94	V2
Fire load	0.015 MJ
Weight	0.5 g

Commercial data

Product Group	26 (picoMAX Connectors)
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 8.0	EC002848
ETIM 7.0	EC002848
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4050821479260
Customs tariff number	82055980000

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
UL Underwriters Laboratories Inc.	UL 1977	E45171

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance 2092-1630



CAD/CAE-Data

CAD data

2D/3D Models
2092-1630




CAE data

ZUKEN Portal
2092-1630




Installation Notes


Locking system



Disconnecting female connector via un-
locking tool. Plug unlocking tool into the
male header's locking latch.



Disconnecting a female connector via un-
locking tool. Plug unlocking tool into the
male header's locking latch.



Pull on both unlocking tool and conduc-
tors to remove female connector from
male header.