

Features

• Simple and slick integral design with no driver box and without any visible screws
New technology utilization for improved performance
Invisible in-track adaptor for an impressive architectural look
Extremely precise light beams due to the high-quality lens #80mm die-cast aluminium body,
Adjustable beam angle: between 8° - 55° , Textured white finishing colour
Light color temperature: 2700K, candle light
System power: 18W, Fixture lumen output: 940lm, efficacy: 52lm/W, Ra97 typical, LED chromacity: 2 step MacAdam ellipse LED source (SDCM2), IR/UV free light source without heat radiation
Operating voltage 220-240V / 50-60Hz, SylSmart SSC suitable for installation on 3-circuit tracks, please check compatibility list on the instruction sheet. Compatible with OneTrack
Electrical protection: Class II. Degree of protection: IP20, suitable for indoor environment only
Horizontal rotation: 355°, vertical tilt: 90°
Nominal product dimensions: D.80mmx215mm
5 years warranty. Suitable for track mounting


Product Overview

Product name	CONCORD BEACON MUSE 2700K SSC WHITE
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Fixture rating	Enclosed
General application	Museums & Galleries, Retail, Hospitality
ETIM Class	EC001744
E-number FI	4170391
Fixture luminous flux (lm)	940

CONCORD BEACON MUSE 2700K SSC WHITE 2062571

Luminaire efficacy (lm/W)	52
LOR (%)	100
Correlated colour temperature (k)	2700
Light colour	Candlelight
CRI (Ra)	97
Colour Variation Initial (SDCM)	2
Beam Angle (°)	55
Photobiological Risk Group	RG1
Total power consumption (W)	18
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Minimum dimming level (%)	1
Housing colour	RAL9016
IP rating	IP20
IK rating	IK02
Product EAN number	5025768625710
Warranty	5 years
Dimming method	SylSmart SSC
Useful luminous flux (#use)	940

Photometry



Technical drawings

