

Features

- LED Panel with backlit technology, ideal for general indoor lighting applications such as breakout areas, offices and meeting rooms. Extruded aluminium frame, passive cooling. Low glaring UGR<22. RG0, 110 degree beam angle , optical system: PS diffuser with Opal finish. Light color temperature: 3000K Warm White, total system power: 30W , total fixture output: 3800lm, efficacy: 127 lm/W, Ra80 typical, LED chromacity: 3 step MacAdam ellipse (SDCM3), lifespan: 100,000 hours at 70% of the original output (L70B50), IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, low flicker, non dimmable driver, electrical protection: Class II. Degree of Protection: IP40/IP20, suitable for indoor environment only. Nominal size: 595x595mm, Loop in / loop out wiring, saftey cables & quick connector included, 25mm nominal height, White color frame, weight: 1,67Kg.

Product Overview


Product name	START Panel 600x600 3800lm 830
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting, Suspended
General application	Education, Office
ETIM Class	EC002892
E-number FI	4279391
Fixture luminous flux (lm)	3800
Luminaire efficacy (lm/W)	127
Colour temperature (K)	3000
Light colour	Warm White

Light your world

START Panel 600x600 3800lm 830 0044635

CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	110
Glare control	< 22
Photobiological Risk Group	RG0
Total power consumption (W)	30
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP40/20
IK rating	IK03
Product EAN number	5410288446356
Warranty	5 years
Dimming method	N/A

Photometry



Technical drawings

